

Page 1 of 16
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.09.2022 / 0017
Replacing version dated / version: 01.11.2021 / 0016
Valid from: 21.09.2022
PDF print date: 23.09.2022
Plastic and Rubber Dressing Premium P309
10 | Art.: 6100 1728, Art.: 6104 1728

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Plastic and Rubber Dressing Premium P309
10 | Art.: 6100 1728, Art.: 6104 1728

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Care product for plastic surfaces

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG
Theo-Förch-Str. 11 – 15
74196 Neuenstadt
Tel.: 07139/95-0
Fax: 07139/95-199
Email: info@foerch.de
Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Flam. Liq.	2	H225-Highly flammable liquid and vapour.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0017
 Replacing version dated / version: 01.11.2021 / 0016
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Plastic and Rubber Dressing Premium P309
 10 | Art.: 6100 1728, Art.: 6104 1728



Danger

H225-Highly flammable liquid and vapour. H304-May be fatal if swallowed and enters airways. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment.
 P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P312-Call a POISON CENTRE / doctor if you feel unwell. P331-Do NOT induce vomiting.
 P403+P233-Store in a well-ventilated place. Keep container tightly closed.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
 Hydrocarbons, C10-C13, n-alkanes, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).
 Dangerous vapours heavier than air.
 In case of spreading near the ground, flashback to distance sources of ignition is possible.

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.
3.2 Mixtures

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Registration number (REACH)	01-2119473851-33-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	920-750-0
CAS	---
content %	50-70
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics	
Registration number (REACH)	01-2119475608-26-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	929-018-5
CAS	---
content %	1-20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Asp. Tox. 1, H304

Page 3 of 16
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.09.2022 / 0017
Replacing version dated / version: 01.11.2021 / 0016
Valid from: 21.09.2022
PDF print date: 23.09.2022
Plastic and Rubber Dressing Premium P309
10 | Art.: 6100 1728, Art.: 6104 1728

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
The substances named in this section are given with their actual, appropriate classification!
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.
Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting - give copious water to drink. Consult doctor immediately.
Danger of aspiration.
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
The following may occur:

Irritation of the skin.
Irritation of the respiratory tract
Headaches
Nausea
Dizziness
Inhalation of fumes may have narcotic effect.
Danger of aspiration.
Oedema of the lungs
Chemical pneumonitis (condition similar to pneumonia)
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.
Pulmonary oedema prophylaxis
Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Cool container at risk with water.
CO2
Exinction powder
Water jet spray
Large fire:
Water jet spray
Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
Oxides of carbon
Toxic gases

Page 4 of 16
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.09.2022 / 0017
Replacing version dated / version: 01.11.2021 / 0016
Valid from: 21.09.2022
PDF print date: 23.09.2022
Plastic and Rubber Dressing Premium P309
10 | Art.: 6100 1728, Art.: 6104 1728

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Ensure sufficient supply of air.
Remove possible causes of ignition - do not smoke.
Take precautions against electrostatic charges.
Avoid inhalation, and contact with eyes or skin.
If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent surface and ground-water infiltration, as well as ground penetration.
Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.
If accidental entry into drainage system occurs, inform responsible authorities.
Danger of explosion.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Avoid aerosol formation.
Keep away from sources of ignition - Do not smoke.
Take precautions against electrostatic charges.
Avoid contact with eyes or skin.
Do not carry cleaning cloths soaked in product in trouser pockets.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Not to be stored in gangways or stair wells.
Store product closed and only in original packing.
Observe special storage conditions.

GB

Page 5 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0017
 Replacing version dated / version: 01.11.2021 / 0016
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Plastic and Rubber Dressing Premium P309
 10 | Art.: 6100 1728, Art.: 6104 1728

Do not store with oxidizing agents.
 Solvent resistant floor
 Protect from direct sunlight and warming.
 Store cool.
 Store in a dry place.
 Suitable container:
 Steel
 Stainless steel (alloy steel)

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 1000 mg/m³

Chemical Name	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
WEL-TWA: 1200 mg/m ³	WEL-STEL: ---	---	
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)		
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)		

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, <2% aromatics		
WEL-TWA: 800 mg/m ³	WEL-STEL: ---	---	
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)		
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)		

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m ³	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.09.2022 / 0017
Replacing version dated / version: 01.11.2021 / 0016
Valid from: 21.09.2022
PDF print date: 23.09.2022
Plastic and Rubber Dressing Premium P309
10 | Art.: 6100 1728, Art.: 6104 1728

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
Applies only if maximum permissible exposure values are listed here.
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
These are specified by e.g. EN 14042.
EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
Chemical resistant protective gloves (EN ISO 374).
Recommended
Protective nitrile gloves (EN ISO 374).
Minimum layer thickness in mm:
0,4
Permeation time (penetration time) in minutes:
> 480
Protective hand cream recommended.
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
If OES or MEL is exceeded.
Filter A P2 (EN 14387), code colour brown, white
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
Not applicable

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
Selection of materials derived from glove manufacturer's indications.
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Colourless
Odour:	Mild
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	>90 °C
Flammability:	Flammable
Lower explosion limit:	~0,8 Vol-% ((Particulars of main substances contained))
Upper explosion limit:	~6,5 Vol-% ((Particulars of main substances contained))

Page 7 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0017
 Replacing version dated / version: 01.11.2021 / 0016
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Plastic and Rubber Dressing Premium P309
 10 | Art.: 6100 1728, Art.: 6104 1728

Flash point:	-10 °C
Auto-ignition temperature:	220 °C
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	<7 mm ² /s (20°C)
Solubility:	Not miscible
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,77 g/ml
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

9.2 Other information

Explosives:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising liquids:	No
Bulk density:	n.a.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Electrostatic charge

Avoid shock and friction

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Plastic and Rubber Dressing Premium P309

10 | Art.: 6100 1728, Art.: 6104 1728

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Page 8 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.09.2022 / 0017

Replacing version dated / version: 01.11.2021 / 0016

Valid from: 21.09.2022

PDF print date: 23.09.2022

Plastic and Rubber Dressing Premium P309

10 | Art.: 6100 1728, Art.: 6104 1728

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2800	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:		2000	mg/kg	Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:	LOAEL	9000	ppm	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion

Page 9 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0017
 Replacing version dated / version: 01.11.2021 / 0016
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Plastic and Rubber Dressing Premium P309
 10 | Art.: 6100 1728, Art.: 6104 1728

Acute toxicity, by inhalation:	LC50	>5,6	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Aerosol
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Repeated exposure may cause skin dryness or cracking., Not irritant, Analogous conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Analogous conclusion, No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 478 (Genetic Toxicology - Rodent dominant Lethal Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 415 (One-Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion

GB

Page 10 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0017
 Replacing version dated / version: 01.11.2021 / 0016
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Plastic and Rubber Dressing Premium P309
 10 | Art.: 6100 1728, Art.: 6104 1728

Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Negative, Analogous conclusion
Aspiration hazard:						Yes

11.2. Information on other hazards

Plastic and Rubber Dressing Premium P309 10 Art.: 6100 1728, Art.: 6104 1728						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Plastic and Rubber Dressing Premium P309 10 Art.: 6100 1728, Art.: 6104 1728							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Photochemical decomposition in the atmosphere. Mechanical precipitation possible.
12.3. Bioaccumulative potential:							Possible
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							According to the recipe, contains no AOX.
Other information:	DOC						DOC-elimination degree(complexing organic substance) \geq 80%/28d: n.a.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.7. Other adverse effects:							Product floats on the water surface.
12.3. Bioaccumulative potential:							Not to be expected(evaporation)
12.4. Mobility in soil:							Product is slightly volatile.

12.1. Toxicity to fish:	NOELR	28d	0,574		Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	3 - 10	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	4,6 - 10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1 -1,6	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	10	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50	72h	10	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Completely biodegradable.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EL50	48h	11,14	mg/l			calculated value

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	77-83	%			Readily biodegradable
12.1. Toxicity to fish:	LL50	96h	>10	mg/l	Oncorhynchus mykiss		Analogous conclusion
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Skeletonema costatum		
12.1. Toxicity to fish:	NOELR	28d	0,139	mg/l	Oncorhynchus mykiss		Analogous conclusion
12.1. Toxicity to daphnia:	NOELR	21d	0,361	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata		Analogous conclusion
12.3. Bioaccumulative potential:							Possible
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:							DOC-elimination degree(complexing organic substance)>= 80%/28d.; n.a.
Other information:	AOX						Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

SECTION 13: Disposal considerations

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0017
 Replacing version dated / version: 01.11.2021 / 0016
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Plastic and Rubber Dressing Premium P309
 10 | Art.: 6100 1728, Art.: 6104 1728

13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:
 The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
 07 02 17 waste containing silicones other than those mentioned in 07 02 16
 Recommendation:
 Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.
 Empty container completely.
 Untampered packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.
 Residues may present a risk of explosion.
 Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 1993

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
 UN 1993 FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM))
 14.3. Transport hazard class(es): 3
 14.4. Packing group: II
 Classification code: F1
 LQ: 1 L
 14.5. Environmental hazards: environmentally hazardous
 Tunnel restriction code: D/E



Transport by sea (IMDG-code)

14.2. UN proper shipping name:
 FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM))
 14.3. Transport hazard class(es): 3
 14.4. Packing group: II
 EmS: F-E, S-E
 Marine Pollutant: Yes
 14.5. Environmental hazards: environmentally hazardous



Transport by air (IATA)

14.2. UN proper shipping name:
 Flammable liquid, n.o.s. (NAPHTHA (PETROLEUM))
 14.3. Transport hazard class(es): 3
 14.4. Packing group: II
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

GB

Page 13 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0017
 Replacing version dated / version: 01.11.2021 / 0016
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Plastic and Rubber Dressing Premium P309
 10 | Art.: 6100 1728, Art.: 6104 1728

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): ~ 78 %
REGULATION (EC) No 648/2004
 30 % and more
 aliphatic hydrocarbons

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Flam. Liq. — Flammable liquid
 Asp. Tox. — Aspiration hazard
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Aquatic Chronic — Hazardous to the aquatic environment - chronic

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
 Guidelines for the preparation of safety data sheets as amended (ECHA).
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
 Safety data sheets for the constituent substances.
 ECHA Homepage - Information about chemicals.
 GESTIS Substance Database (Germany).
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS
ZAE Le Marchais Renard
CS 50125 Montereau-sur-le-Jard
77019 Melun Cedex
Frankreich
Tel. +33 1 64 14 48 48
Fax. +33 1 64 14 48 49
E-Mail: info@forch.fr
Internet: www.forch.fr

S.C. Foerch S.R.L.
Str. Zizinului nr.110
500407 Brasov
Rumänien
Tel. +40 368 408192
Fax. +40 368 408193
E-Mail: info@foerch.ro
Internet: www.foerch.ro

Foerch AG
Muttenerstrasse 143
4133 Pratteln
Schweiz
Tel. +41 61 8262031
Fax. +41 61 8262039
E-Mail: info@foerch.ch
Internet: www.foerch.ch

Foerch Bulgaria EOOD
475 Botevgradsko Shose Blvd.
BG 1517 Sofia, Bulgaria
Tel. 00359 2 981 2841
Fax. 00359 982 10 30 86
E-Mail: info@foerch.bg

Förch d.o.o.
Buzinska cesta 58
10010 Zagreb
Kroatien
Tel. +385 1 2912900
Fax. +385 1 2912901
E-Mail: info@foerch.hr
internet: www.foerch.hr

Theo Förch GmbH
Röcklbrunnstraße 39A
5020 Salzburg
Österreich
Tel. +43 662 875574-0
Fax +43 662 878677-21
Verkauf Tel. +43 662 875574-900
Verkauf Fax +43 662 875574-30
E-Mail: info@foerch.at
Internet: www.foerch.at

Förch Componentes para Taller S.L.
Camino de San Antón, S/N
18102 Ambroz (Granada)
Spanien
Tel. +34 958 40 17 76
Fax. +34 958 40 17 87
E-Mail: info@forch.es
Internet: www.forch.es

Förch A/S
Hagemannsvej 3
8600 Silkeborg
Dänemark
Tel. +45 86 823711
Fax. +45 86 800617
E-Mail: info@foerch.dk
Internet: www.foerch.dk

Lhomme Tools & Fasteners BV
Seinhuisstraat 5 B4
Poort 0331
3600 Genk
Belgien
Tel. +32 89 71 66 61
E-Mail: info@lhommetools.be
Internet: www.lhommetools.be

Ziebe Limited
7 Century Court, Westcott,
Aylesbury, Bucks, HP18 0XP (UK)
Grossbritannien
Tel +44 12 96 65 52 82
E-Mail: sales@ziebe.co.uk
Internet: www.ziebe.co.uk

Förch Polska Sp. z o.o.
Mikdyrzecze Gorne 379
43-392 K/Bielska-Bialej
Polen
Tel. +48 338196000
Fax. +48 338158548
E-Mail: info@forch.pl
Internet: www.forch.pl

Vardalis SM P.C.
Ethnikis Antistasis 62
57007 Chalkidona-Thessaloniki
Griechenland
Tel. +30 23910 21222
Fax. +30 23910 21223
E-Mail: info@forch.gr
Internet: www.forch.gr

Förch Kereskedelmi Kft
Börgöndi út 14
8000 Székesfehérvár
Ungarn
Tel. +36 22 348348
Fax. +36 22 348355
E-Mail: info@foerch.hu
Internet: www.foerch.hu

Förch S.r.l.
Via Antonio Stradivari 4
39100 Bolzano (BZ)
Italien
Tel. +39 0471 204330
Fax: +39 0471 204290
E-Mail: info@forch.it
Internet: www.forch.it

Förch Nederland BV
Twentepoort Oost 51
7609 RG Almelo
Niederlande
Tel. +31 85 77 32 420
E-Mail: info@foerch.nl
Internet: www.foerch.nl

AB varahlutir ehf
Funahöfði 9
110 Reykjavík
Tel. +354 567 6020
E-mail: ab@ab.is
Internet: www.ab.is

Förch Slovensko s.r.o.
Rosinská cesta 8
010 08 Žilina
Slowakei
Tel +421 41 5002454
E-Mail: info@forch.sk
Internet: www.forch.sk

Förch Sverige AB
Brännarevägen 1
151 55 Södertälje
Schweden
Tel. +46 855089264
E-mail: info@foerch.se
Internet: www.foerch.se

Page 15 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0017
 Replacing version dated / version: 01.11.2021 / 0016
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Plastic and Rubber Dressing Premium P309
 10 | Art.: 6100 1728, Art.: 6104 1728

Förch, s.r.o.
 Dopravní 1314/1
 104 00 Praha 10 – Uhřetínoves
 Tschechien
 Tel. +420 271 001 984-9
 E-Mail: info@foerch.cz
 Internet: www.foerch.cz

FORCH d.o.o.
 Ljubljanska cesta 51A
 1236 Trzin
 Slowenien
 Tel. +386 1 2442490
 Fax. +386 1 2442492
 E-Mail: info@foerch.si
 Internet: www.foerch.si

Forch Australia
 2 Forward Street
 Gnangara WA 6077
 Tel. +61 (08) 9303 9113
 Fax. +61 (08) 9303 9114
 Emergency telephone: +614 13 550 330
 Email : sales@forch.com.au
 Internet: www.forch.com.au

Troscoe Ltd
 Unit 6, 13 Highbrook Drive
 East Tamaki 2013, New Zealand
 Tel: +64 21 081 30780 / +64 21 024 05583
 Email:sales@forchnz.co.nz
 Internet: www.forchnz.co.nz

Förch Portugal Lda
 Centro Empresarial Sintra-Estoril III
 Rua Pé de Mouro, Nr 33, Armazém J
 2710-335 Sintra
 Portugal
 Tel. +351 917314442
 E-Mail: info@forch.pt
 Internet: www.forch.pt

Trigers SIA
 Straupes iela 3
 1073 Riga
 Lettland
 Tel. +371 6 7 90 25 15
 Fax. +371 67 90 24 96
 E-Mail: trigers@trigers.lv
 Internet: www.trigers.lv

Förch Otom.Ins.ve San.Ürün.Paz.Ltd.Sti.
 Haramidere Mevkii Beysan Sanayi
 Sitesi Birlik Caddesi No:6/3
 34524 Beylikdüzü / Istanbul
 Türkei
 Tel. +90 (0)212 422 8744-45
 Fax. +90 (0)212 422 8788
 E-Mail: info@forch.com.tr
 Internet: www.forch.com.tr

Total Consumables Ltd
 Coolnafearagh
 Monasterevin
 Co. Kildare
 W34 TX29
 Irland
 Tel. +353871271473

Venus Arma d.o.o.
 Partner Theo Förch GmbH & Co. KG
 Batajnicksi drum 18a
 11080 Zemun
 Republika Srbija
 Tel. +381 11 407-20-91
 Fax. +381 11 407-20-91
 E-Mail: office@foerch.rs
 Internet: www.foerch.rs

Any abbreviations and acronyms used in this document:

- acc., acc. to according, according to
- ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
- AOX Adsorbable organic halogen compounds
- approx. approximately
- Art., Art. no. Article number
- ASTM ASTM International (American Society for Testing and Materials)
- ATE Acute Toxicity Estimate
- BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
- BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
- BCF Bioconcentration factor
- BSEF The International Bromine Council
- bw body weight
- CAS Chemical Abstracts Service
- CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
- CMR carcinogenic, mutagenic, reproductive toxic
- DMEL Derived Minimum Effect Level
- DNEL Derived No Effect Level
- DOC Dissolved organic carbon
- dw dry weight
- e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
- EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
- EC European Community
- ECHA European Chemicals Agency
- ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
- EEC European Economic Community

EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EN	European Norms
EPA	United States Environmental Protection Agency (United States of America)
ErCx, EµCx, ErLx (x = 10, 50)	Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc.	et cetera
EU	European Union
EVAL	Ethylene-vinyl alcohol copolymer
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
Koc	Adsorption coefficient of organic carbon in the soil
Kow	octanol-water partition coefficient
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC (Code)	International Bulk Chemical (Code)
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCRID	International Uniform Chemical Information Database
IUPAC	International Union for Pure Applied Chemistry
LC50	Lethal Concentration to 50 % of a test population
LD50	Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc	Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow	Logarithm of octanol-water partition coefficient
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
NIOSH	National Institute for Occupational Safety and Health (USA)
NLP	No-longer-Polymer
NOEC, NOEL	No Observed Effect Concentration/Level
OECD	Organisation for Economic Co-operation and Development
org.	organic
OSHA	Occupational Safety and Health Administration (USA)
PBT	persistent, bioaccumulative and toxic
PE	Polyethylene
PNEC	Predicted No Effect Concentration
ppm	parts per million
PVC	Polyvinylchloride
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No.	9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID	Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC	Substances of Very High Concern
Tel.	Telephone
TOC	Total organic carbon
UN RTDG	United Nations Recommendations on the Transport of Dangerous Goods
VOC	Volatile organic compounds
vPvB	very persistent and very bioaccumulative
wwt	wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.

Nummer:

BETRIEBSANWEISUNG gem. § 14 GefStoffV.

Betrieb:

Datum:

Bearbeiter:

Verantwortlicher:

Arbeitsbereich:

Arbeitsplatz / Tätigkeit:

GEFAHRSTOFFBEZEICHNUNG

Leichtentzündliche Produkte, gesundheitsschädlich

Es können die folgenden gefährlichen Stoffe enthalten sein:

Kohlenwasserstoffe, C6-C7, n-Alkane, Isoalkane, Cycloalkane, <5% n-Hexan, Ethylacetat, Cyclohexan, Naphtha (Erdöl), mit Wasserstoff behandelte leicht, Kolophonium, Cyclene, Orangenextrakt, Naturkautschuk

GEFAHREN FÜR MENSCH UND UMWELT

Diese Betriebsanweisung gilt für die folgenden Produkte:



Gefahr

GHS-EINSTUFUNG NACH VERORDNUNG (EG) 1272/2008

Flüssigkeit und Dampf leicht entzündbar.

Verursacht Hautreizungen. Kann allergische Reaktionen verursachen.

Kann bei Einatmen Allergie, asthmaartige Symptome oder Atembeschwerden verursachen.

Kann bei Verschlucken und Eindringen in die Atemwege tödlich sein.

Kann Schläfrigkeit und Benommenheit verursachen.

Giftig für Wasserorganismen, mit langfristiger Wirkung.

Komplexe Kombination von Kohlenwasserstoffen. Die beinhalteten Lösemittel können über die Atemwege aufgenommen werden. Beim Einatmen hoher Lösungsmittelkonzentrationen können Reizungen an den Augen, Atemwegen und Schleimhäuten auftreten. Als Symptome können Rausch, Schwindel, Bewegungsstörungen, Schläfrigkeit, Übelkeit, Appetitlosigkeit, Erbrechen auftreten. Daneben wirken sie entfettend auf die Haut.

SCHUTZMASSNAHMEN UND VERHALTENSREGELN



Hygienevorschriften:

Nach Produktentnahme darauf achten, dass an der Außenverpackung keine Produktreste anhaften. Berührung mit den Augen, der Haut und der Kleidung vermeiden. Vor den Pausen und bei Arbeitsende Hände gründlich waschen. Vor dem Arbeitsbeginn und nach Pausen Hautschutzsalbe auftragen. Langärmelige Arbeitsschutzkleidung verwenden. Produkt sofort mit geeignetem Reinigungsmittel von der Haut entfernen. Keine Lösungsmittel verwenden. Das Essen, Trinken, Rauchen, sowie die Aufbewahrung von Lebensmitteln im Arbeitsraum ist verboten. Während des Umgangs mit dem Produkt keine Nahrungs- und Genussmittel aufnehmen.

Technische und organisatorische Schutzmaßnahmen zur Verhütung einer Exposition:

Bei der Anwendung des Produktes für gute Be- und Entlüftung sorgen.

Auf Sauberkeit am Arbeitsplatz achten. Verspritzen vermeiden.

Persönliche Schutzausrüstung:

Schutzbrille dichtschießend mit Seitenteilen verwenden.

Chemikalienbeständige Schutzhandschuhe (nach DIN EN 374) aus geeignetem Material wie z. B. Gummi, PVC, Neopren, Latex, oder Butylkautschuk tragen.

Bei Auftreten von Dämpfen oder unzureichender Belüftung oder bei Überschreitung des Arbeitsplatzgrenzwertes Atemschutzmaske benutzen. Weitere Angaben zu der geeigneten Schutzausrüstung finden Sie unter Punkt 8 im Sicherheitsdatenblatt des jeweiligen Produktes.

Beschränkungen für Beschäftigte:

Der Umgang mit Gefahrstoffen ist für Jugendliche nur erlaubt, wenn es zur Erreichung des Ausbildungsziels erforderlich ist. Dabei müssen die Jugendlichen mindestens 16 Jahre alt sein und durch einen Fachkundigen beaufsichtigt werden.

VERHALTEN IM GEFAHRFALL**Geeignete und ungeeignete Löschmittel:**

Geeignete Löschmittel sind Wassersprühstrahl und Feuerlöscher mit Pulver für die Brandklassen A, B, C, sowie Kohlendioxidlöscher. Brände nicht mit Wasservollstrahl löschen.

Aufsaug- und Bindemittel, Neutralisationsmittel:

Verschüttete Reste mit nicht brennbarem Bindemittel aufnehmen und sachgerecht entsorgen.

Zusätzliche technische Schutzmaßnahmen und persönliche Schutzausrüstung:

Alle Zündquellen beseitigen. Hautkontakt und Inhalation des Stoffes vermeiden. Bei Brand oder starkem Erwärmen ist die Bildung von explosionsfähigen Dampf- / Luftgemischen sowie giftigen Zersetzungsprodukten möglich. Chemikalienbeständige Schutzkleidung verwenden.

Verschmutzte Kleidung sofort wechseln und erst nach deren Reinigung wieder benutzen.

Bei Bränden den gefährdeten Bereich räumen, betroffene Umgebung warnen.

Persönliche Schutzausrüstung verwenden.

Notwendige Maßnahmen gegen Umweltgefährdungen:

Löschwasser nicht in den Boden, das Grundwasser oder die Kanalisation gelangen lassen.

Aushang Flucht- und Rettungswegpläne:

Aushang Alarmpläne:

NOTRUF:**ERSTE HILFE****Augenkontakt:**

Auge unter Schutz des unverletzten Auges 10 Minuten unter fließendem Wasser bei weit gespreizten Lidern spülen. Für ärztliche Behandlung sorgen.

Hautkontakt:

Benetzte Kleidung entfernen, dabei Selbstschutz beachten. Betroffene Hautpartien sofort gründlich unter fließendem Wasser mit Seife reinigen. Nach großflächigem Kontakt oder bei anhaltenden Reizungen für ärztliche Behandlung sorgen.

Einatmen:

Verletzten unter Selbstschutz aus dem Gefahrenbereich an die frische Luft bringen.

Verletzten ruhig lagern, vor Unterkühlung schützen. Bei Bewusstlosigkeit und vorhandener Atmung stabile Seitenlage. Für ärztliche Behandlung sorgen.

Verschlucken:

Nach versehentlicher Aufnahme von den oben genannten Produkten Mund ausspülen, Flüssigkeit wieder ausspucken. Sofort - bei erhaltenem Bewusstsein - reichlich Flüssigkeit (Wasser) trinken lassen. Für ärztliche Behandlung sorgen.

Verbrennungen:

Verbrannte Hautflächen mit fließendem Wasser kühlen. Für ärztliche Behandlung sorgen.

Ersthelfer:

Erste Hilfe Einrichtungen:

NOTRUF:**SACHGERECHTE ENTSORGUNG**

Mit Tüchern oder Universalbindemittel gründlich aufnehmen und Boden reinigen. Dabei geeignete Schutzausrüstung verwenden. Gebinde restlos entleeren und Hinweis auf der Verpackung beachten.

Entsorgungsbehälter / Sammelstelle

Aufsaugmittel:

Reinigungsmittel:

Erstellt am:

Unterschrift
Verantwortlicher:

Schutzmaßnahmen

Gemäß § 6 GefStoffV ist der Arbeitgeber verpflichtet, eine Gefährdungsbeurteilung durchzuführen. Diese Gefährdungsbeurteilung muss vor Aufnahme der Tätigkeiten durchgeführt werden. Dabei muss zunächst festgestellt werden, ob die Beschäftigten Tätigkeiten mit Gefahrstoffen durchführen oder ob Gefahrstoffe bei diesen Tätigkeiten entstehen oder freigesetzt werden. Ist dies der Fall, so hat er alle hiervon ausgehenden Gefährdungen für die Gesundheit und Sicherheit der Beschäftigten zu beurteilen. Als Ergebnis dieser Gefährdungsbeurteilung werden die für den Schutz der Beschäftigten Maßnahmen festgelegt. Dabei wird zwischen den allgemein notwendigen Maßnahmen und zusätzlich zu treffenden Maßnahmen unterschieden. Die allgemein notwendigen Maßnahmen müssen bei allen Tätigkeiten mit Gefahrstoffen ergriffen werden. Die gemäß § 8 GefStoffV zu treffenden Maßnahmen haben wir für Sie in einer Checkliste zusammengestellt, die Sie als Anlage zu diesem Dokument finden.

Anlage I Allgemeine und zusätzliche Schutzmaßnahmen

Gehen von dem Produkt weitere Gefahren aus, sind zusätzliche Maßnahmen erforderlich. Diese zusätzlichen Maßnahmen sind in den §§ 9 - 11 GefStoffV beschrieben. Dabei hängen die zusätzlichen Maßnahmen von den Eigenschaften der betroffenen Produkte ab. Die dann zu treffenden Maßnahmen haben wir Ihnen in der Anlage II ebenfalls in einer Checkliste zusammengestellt.

Anlage II Allgemeine Schutzmaßnahmen

Produkte, die Maßnahmen gemäß § 10 GefStoffV erforderlich machen, also krebserzeugende, erbgutverändernde und fruchtbarkeitsgefährdende Gefahrstoffe werden nicht von der Theo Förch GmbH & Co. KG vertrieben.

Zuordnung

Um Ihnen die Entscheidung zu erleichtern, welche Maßnahmen im Arbeitsschutz ergriffen werden müssen (allgemeine Maßnahmen oder allgemeine + zusätzliche Maßnahmen) liefern wir Ihnen entsprechende Hinweise in unserer EDV. Hier sind allen Produkten die erforderlichen Schutzmaßnahmen zugeordnet. Dabei steht

AS für Allgemeine Schutzmaßnahmen und
ZS für Allgemeine und zusätzliche Schutzmaßnahmen

Die Zuordnung der Produkte zu den erforderlichen Schutzmaßnahmen erfolgt aus der Kennzeichnung des Produktes, die im Punkt 2 des Sicherheitsdatenblattes angegeben ist. Hier sind zu jedem vergebenen R-Satz / H-Satz die Schutzmaßnahmen der Gefahrstoffverordnung zugeordnet.

Ist dem Produkt kein R-Satz / H-Satz zugeordnet, erfolgt eine Zuordnung zu den allgemeinen Schutzmaßnahmen gemäß § 8 der Gefahrstoffverordnung (Dieses erfolgt auch für Produkte, bei denen aufgrund Ihrer Kennzeichnung und der geringen Produktmenge (kleiner 125 ml) eine Kennzeichnung mit R-Sätzen / H-Sätzen nicht erforderlich ist.

Die Zuordnung der erforderlichen Schutzmaßnahmen zu den R-Sätzen / H-Sätzen erfolgt nach den folgenden Kriterien:

Allgemeine Schutzmaßnahmen gemäß § 8 GefStoffV

Produkte, die lediglich geringe Gefährdungen hervorrufen können. Hier wurden vor allem Produkte zugeordnet, für die die Vergabe eines Gefahrensymbols, oder eines Piktogramms nicht erforderlich ist.

Zusätzliche Schutzmaßnahmen gemäß § 9 GefStoffV

Für reizende / ätzende / gesundheitsschädliche und giftige Stoffe sowie C/M/R-Stoffe der Kat. 3 sind zusätzlich zu den allgemeinen Schutzmaßnahmen weitere Schutzmaßnahmen erforderlich. Diese Maßnahmen sind im § 9 GefStoffV beschrieben. Wird lediglich mit geringen Mengen umgegangen oder sind die Verfahren so, dass kein Kontakt zu diesen Stoffen besteht, können auch die allgemeinen Schutzmaßnahmen nach § 8 ausreichend sein. Wird hingegen mit größeren Mengen hantiert und besteht direkter Kontakt zu diesen Stoffen, sind die zusätzlichen Schutzmaßnahmen gemäß § 9 erforderlich.

Wichtiger Hinweis

Die Zuordnung der Schutzmaßnahmen erfolgte lediglich aufgrund der Kennzeichnung der verwendeten Produkte. Nicht berücksichtigt wurden dabei Stoffmenge, Exposition und Arbeitsverfahren. Daher stellen die angegebenen Schutzmaßnahmen lediglich eine Empfehlung dar, die den Anwender bei seiner Ermittlungspflicht nach § 6 GefStoffV bzw. § 5 des Arbeitsschutzgesetzes unterstützen sollen. Zur endgültigen Festlegung der notwendigen Schutzmaßnahmen ist eine Gefährdungsanalyse vor Ort notwendig, bei der auch die verwendeten Arbeitsmittel und Verfahren, die Exposition gegen die verwendeten Stoffe, mögliche Wechselwirkungen der eingesetzten Produkte, Brand- und Explosionsgefahren sowie Gefährdungen durch Wartungsaufgaben berücksichtigt werden. Weitere zum Teil sehr ausführliche Erläuterungen zur Vorgehensweise bei der Erstellung der Gefährdungsbeurteilung finden Sie in der TRGS 400 sowie in der BGI 570 bzw. BGI 571.

Allgemeine Schutzmaßnahmen (geringe Gefährdung)

Tätigkeiten mit geringer Gefährdung sind Tätigkeiten, bei denen aufgrund der Arbeitsbedingungen einer nur geringen verwendeten Stoffmenge und einer nach Höhe und Dauer niedrigen Exposition die allgemeinen Maßnahmen gemäß § 8 GefStoffV ausreichen. Zur Festlegung von allgemeinen Maßnahmen nach gemäß § 8 GefStoffV müssen die folgenden Bedingungen zutreffen:

Der verwendete Gefahrstoff darf nicht als giftig, sehr giftig, bzw. krebserzeugend, erbgutverändernd oder fruchtbarkeitsgefährdend (Kategorie 1 oder 2) eingestuft sein. Die bei der Tätigkeit verwendete Stoffmenge muss gering sein. Ein eindeutiger Maßstab für »geringe Menge« lässt sich allgemein nicht angeben, da hier auch die gefährlichen Stoffeigenschaften, das Freisetzungsvermögen des Gefahrstoffes und die konkrete Tätigkeit zu berücksichtigen sind. Dabei muss die Exposition nach Höhe und Dauer niedrig sein. Hierbei sind inhalative und dermale Anteile zu berücksichtigen. So liegt z. B. bei Feststoffen eine niedrige inhalative Exposition im Regelfall bei emissionsarmen Verwendungsformen wie Pasten, Wachsen, Granulaten, Pellets, Masterbatches vor.

Tätigkeiten mit Gefahrstoffen in engen Räumen und Behältern sind grundsätzlich keine Tätigkeiten mit geringer Gefährdung.

Die Beurteilung, ob hinsichtlich einer dermalen Exposition die Bedingungen für Tätigkeiten geringer Gefährdung erfüllt sind, kann mit Hilfe der TRGS 401 erfolgen. Aufgrund dieser Vorgaben kann bei Gefahrstoffen, die das Symbol „ätzend“ (R34, R35) tragen, eine Tätigkeit geringer Gefährdung nicht vorliegen, wenn ein Hautkontakt nicht ausgeschlossen werden kann.

Beispiele für Tätigkeiten geringer Gefährdung sind:

Verwendung von Gefahrstoffen, die für den privaten Endverbraucher im Einzelhandel in Selbstbedienung erhältlich sind, z. B. Ausbesserung kleiner Lackschäden mit Lackstiften oder die Verwendung und Aufbewahrung haushaltsüblicher Mengen von Klebstoffen im Haushalt. Auch wenn bei einer Tätigkeit nicht alle Bedingungen nach Absatz 2 erfüllt sind, so kann die Gefährdungsbeurteilung trotzdem zu einer Festlegung von Maßnahmen führen, die weitgehend dem § 8 GefStoffV entsprechen. In diesen Fällen sind jedoch weitere organisatorische Anforderungen zu beachten, insbesondere zum Führen eines Gefahrstoffverzeichnis, der Erstellung einer Betriebsanweisung, der Dokumentation der Gefährdungsbeurteilung und zur arbeitsmedizinischen Vorsorge.

Bei Tätigkeiten mit geringer Gefährdung sind die folgenden Schutzmaßnahmen zu beachten:

- Nur die vom Arbeitgeber vorgesehenen Gefahrstoffe verwenden.
- Nur die benötigten Gefahrstoffe am Arbeitsplatz aufbewahren.
- Arbeitsplatz aufräumen sowie Arbeitsgeräte und Werkzeuge sauber halten.
- Verunreinigungen durch Gefahrstoffe sofort beseitigen.
- Rückstände von Gefahrstoffen an Behältern entfernen.
- Gefahrstoffe so aufbewahren, dass Missbrauch und Fehlgebrauch verhindert werden.
- Gefahrstoffe möglichst in der Originalverpackung aufbewahren.
- Gefahrstoffe nicht in solchen Behältern aufbewahren oder lagern, durch deren Form oder Inhalt Gefahrstoffe mit Lebensmitteln verwechselt werden können.
- Gefahrstoffe nicht in der Nähe von Arzneimitteln, Lebensmitteln oder Futtermitteln aufbewahren
- Zur Vermeidung einer inhalativen Belastung ist im Regelfall eine natürliche Lüftung ausreichend.

Zusätzliche Schutzmaßnahmen gemäß § 9 GefStoffV

Der Arbeitgeber hat Maßnahmen so festzulegen, dass die durch einen Gefahrstoff bedingte Gefährdung der Gesundheit und Sicherheit der Beschäftigten bei der Arbeit beseitigt oder auf ein Minimum reduziert wird. Es gilt das Substitutionsgebot, das heißt, falls Produkte verfügbar sind, von denen eine geringere Gefährdung ausgeht, sind diese Produkte zu verwenden. Lässt sich die Gefährdung nicht beseitigen, hat der Arbeitgeber diese durch Maßnahmen nach dem Stand der Technik und einer guten Arbeitspraxis in der nachstehenden Rangordnung auf ein Minimum zu verringern:

- Gestaltung geeigneter Verfahren und technischer Steuerungseinrichtungen sowie Verwendung geeigneter Arbeitsmittel und Materialien,
- Durchführung kollektiver Schutzmaßnahmen an der Gefahrenquelle, wie zum Beispiel angemessene Be- und Entlüftung und geeignete organisatorische Maßnahmen. Die Gefährdung ist auf ein Minimum reduziert, wenn z. B.
 - der Stand der Technik eingehalten wird,
 - ein Arbeitsplatzgrenzwert eingehalten wird,
 - Hautkontakt verhindert wird,
 - die Bildung explosionsfähiger Atmosphäre verhindert wird oder
 - Zündquellen beseitigt sind.

Kann eine Gefährdung nicht durch diese Maßnahmen beseitigt werden, sind individuelle Schutzmaßnahmen, wie das Tragen von persönlicher Schutzausrüstung notwendig.

Gemäß § 14 GefStoffV sind die Beschäftigten auf der Basis der schriftlich vorliegenden Betriebsanweisung mindestens einmal jährlich mündlich zu unterweisen. Die Mindestangaben zur schriftlichen Betriebsanweisung und die Mindestforderungen zur Unterweisung sind in der TRGS 555 „Betriebsanweisung und Information der Beschäftigten“ aufgeführt.

Für bestimmte Tätigkeiten sind arbeitsmedizinische Vorsorgeuntersuchungen notwendig. Die Tätigkeiten und Stoffe für die das gilt, sind in den §§ 15, 16 und dem Anhang V GefStoffV aufgeführt.

Weitere Unterstützung bei der Festlegung der betrieblichen Grundmaßnahmen bieten die Schutzleitfäden der Reihe 200 (siehe www.baua.de und www.bgchemie.de).

Firmenlogo	Erfassung der erforderlichen Schutzmaßnahmen Allgemeine und zusätzliche Schutzmaßnahmen nach §§ 8, 9 und 11 GefStoffV - Gefährdungsbeurteilung - Dokumentation -	Datum: Betrieb:
------------	--	--------------------

Tätigkeit/Personen:

Gefahrstoffe

Anforderung nach §§ 8, 9 und 11 GefStoffV

Nr.	Maßnahmen	Erfüllt		Schutzmaßnahmen (technisch-organisatorisch-persönlich)	Beratungs bedarf	Realisierung		Wirksamkeit	
		ja	nein			Bis wann	durch	wirksam	wann
1.	Informationsermittlung und innerbetriebliche Kennzeichnung								
1.1.	Gefahrstoffverzeichnis liegt vor	<input type="checkbox"/>	<input type="checkbox"/>						
1.2.	Sicherheitsdatenblätter sind vorhanden, aktuell (2)	<input type="checkbox"/>	<input type="checkbox"/>						
1.3.	Sicherheitsdatenblätter sind den Mitarbeitern zugänglich (2)	<input type="checkbox"/>	<input type="checkbox"/>						
1.4.	Gefahrstoffe sind eindeutig gekennzeichnet (2)	<input type="checkbox"/>	<input type="checkbox"/>						
1.5.	Rohrleitungen und Anlagenteile sind eindeutig gekennzeichnet	<input type="checkbox"/>	<input type="checkbox"/>						
2.	Arbeitsstätte								
2.1.	Eine gute allgemeine Lüftung, ggf. technische Lüftung ist vorhanden	<input type="checkbox"/>	<input type="checkbox"/>						
2.2.	Pausenräume und Bereitschaftsräume stehen zur Verfügung (2)	<input type="checkbox"/>	<input type="checkbox"/>						
2.3.	Waschgelegenheiten mit Handtüchern sind vorhanden	<input type="checkbox"/>	<input type="checkbox"/>						
2.4.	Reinigungsmittel, Hautschutz- und Hautpflegemittel sind vorrätig	<input type="checkbox"/>	<input type="checkbox"/>						
2.5.	Umkleieräume und Kleiderablagen stehen zur Verfügung (2)	<input type="checkbox"/>	<input type="checkbox"/>						
2.6.	Die Arbeitsplätze werden regelmäßig gereinigt	<input type="checkbox"/>	<input type="checkbox"/>						
2.7.	Technische Schutzmaßnahmen werden spätestens jedes dritte Jahr geprüft und dokumentiert	<input type="checkbox"/>	<input type="checkbox"/>						
3.	Arbeitsverfahren								
3.1.	Es wurde eine Substitutionsprüfung durchgeführt (2)	<input type="checkbox"/>	<input type="checkbox"/>						
3.2.	Es werden Arbeitsverfahren angewendet, die möglichst wenig Gase, Dämpfe, Stäube und Aerosole verursachen	<input type="checkbox"/>	<input type="checkbox"/>						
3.3.	Es werden geeignete Arbeitsmittel, Geräte und Anlagen bereitgestellt	<input type="checkbox"/>	<input type="checkbox"/>						
3.4.	Die Anzahl der Exponierten ist auf ein Minimum reduziert	<input type="checkbox"/>	<input type="checkbox"/>						
3.5.	Die Rangfolge der Schutzmaßnahmen wurde eingehalten (2)	<input type="checkbox"/>	<input type="checkbox"/>						
3.6.	Gebinde sind geschlossen und werden nur zur Entnahme geöffnet	<input type="checkbox"/>	<input type="checkbox"/>						

Firmenlogo	Erfassung der erforderlichen Schutzmaßnahmen Allgemeine und zusätzliche Schutzmaßnahmen nach §§ 8, 9 und 11 GefStoffV - Gefährdungsbeurteilung - Dokumentation -	Datum: Betrieb:
------------	--	--------------------

Tätigkeit/Personen:

Gefahrstoffe

Anforderung nach §§ 8, 9 und 11 GefStoffV

Nr.	Maßnahmen	Erfüllt		Schutzmaßnahmen (technisch-organisatorisch-persönlich)	Beratungsbedarf	Realisierung		Wirksamkeit	
		ja	nein			Bis wann	durch	wirksam	wann
3.7.	Die Dauer und das Ausmaß der Exposition ist auf das erforderliche Maß beschränkt	<input type="checkbox"/>	<input type="checkbox"/>						
3.8.	Bei Abfüll- und Umfüllvorgängen wird ausreichend belüftet und abgesaugt	<input type="checkbox"/>	<input type="checkbox"/>						
3.9.	Ablagerungsmöglichkeiten für Stäube sind gering gehalten	<input type="checkbox"/>	<input type="checkbox"/>						
3.10.	Verspritzen von Flüssigkeiten wird vermieden	<input type="checkbox"/>	<input type="checkbox"/>						
4.	Organisation								
4.1.	Gefahrstoffmenge am Arbeitsplatz wird gering gehalten	<input type="checkbox"/>	<input type="checkbox"/>						
4.2.	Arbeitsmittel und Stoffe werden bestimmungsgemäß verwendet	<input type="checkbox"/>	<input type="checkbox"/>						
4.3.	Die Beschäftigten werden mindestens einmal jährlich unterwiesen	<input type="checkbox"/>	<input type="checkbox"/>						
4.4.	Die Unterweisung schließt eine arbeitsmedizinisch-toxikologische Beratung ein (2)	<input type="checkbox"/>	<input type="checkbox"/>						
4.5.	Betriebsanweisungen sind vorhanden und den Beschäftigten bekannt (2)	<input type="checkbox"/>	<input type="checkbox"/>						
4.6.	Bei Alleinarbeit ist eine angemessene Aufsicht gewährleistet (2)	<input type="checkbox"/>	<input type="checkbox"/>						
4.7.	Arbeitsplatzgrenzwerte (AGW) werden eingehalten (2)	<input type="checkbox"/>	<input type="checkbox"/>						
4.7.	Bei Stoffen ohne AGW wurde die Wirksamkeit der Schutzmaßnahmen nachgewiesen (2)	<input type="checkbox"/>	<input type="checkbox"/>						
4.8.	Arbeitsmedizinische Vorsorgeuntersuchungen wurden veranlasst (2)	<input type="checkbox"/>	<input type="checkbox"/>						
4.9.	Arbeitsmedizinische Vorsorgeuntersuchungen wurden angeboten (2)	<input type="checkbox"/>	<input type="checkbox"/>						
4.10.	Nachuntersuchungen werden regelmäßig durchgeführt (2)	<input type="checkbox"/>	<input type="checkbox"/>						
5.	PSA								
5.1.	PSA gegen inhalative und dermale Gefährdungen ist geeignet und verwendungsfähig	<input type="checkbox"/>	<input type="checkbox"/>						
5.2.	Das Tragen von belastender PSA ist zeitlich auf ein Mindestmaß beschränkt (2)								
5.3.	PSA gegen physikalisch-chemische Gefährdungen ist geeignet	<input type="checkbox"/>	<input type="checkbox"/>						

Firmenlogo	Erfassung der erforderlichen Schutzmaßnahmen Allgemeine und zusätzliche Schutzmaßnahmen nach §§ 8, 9 und 11 GefStoffV - Gefährdungsbeurteilung - Dokumentation -	Datum: Betrieb:
------------	--	--------------------

Tätigkeit/Personen:

Gefahrstoffe

Anforderung nach §§ 8, 9 und 11 GefStoffV

Nr.	Maßnahmen	Erfüllt		Schutzmaßnahmen (technisch-organisatorisch-persönlich)	Beratungs bedarf	Realisierung		Wirksamkeit	
		ja	nein			Bis wann	durch	wirksam	wann
6.	Hygiene und Hautschutz¹⁾								
6.1.	Arbeitskleidung sollte getragen werden	<input type="checkbox"/>	<input type="checkbox"/>						
6.2.	Essen, Trinken, Rauchen sollte am Arbeitsplatz verboten werden	<input type="checkbox"/>	<input type="checkbox"/>						
6.3.	Kontaminationen und Verschmutzungen der Haut werden sofort entfernt	<input type="checkbox"/>	<input type="checkbox"/>						
6.4.	Verschmutzte Arbeitsbekleidung wird ausgewechselt	<input type="checkbox"/>	<input type="checkbox"/>						
6.5.	Staubige Arbeitsbekleidung wird gereinigt	<input type="checkbox"/>	<input type="checkbox"/>						
6.6.	Es liegt ein Hautschutzplan vor	<input type="checkbox"/>	<input type="checkbox"/>						
6.7.	Es erfolgt eine getrennte Aufbewahrung von Straßen- und Arbeitsbekleidung (2)	<input type="checkbox"/>	<input type="checkbox"/>						
7.	Sauberkeit und Reinigung								
7.1.	Arbeitsplätze werden regelmäßig aufgeräumt	<input type="checkbox"/>	<input type="checkbox"/>						
7.2.	Arbeitsplätze/Arbeitsbereiche werden regelmäßig gereinigt	<input type="checkbox"/>	<input type="checkbox"/>						
7.3.	Arbeitsmittel, Geräte und Gebinde werden gereinigt und sauber gehalten	<input type="checkbox"/>	<input type="checkbox"/>						
7.4.	Abfallbehältnisse zur ordnungsgemäßen Entsorgung stehen bereit	<input type="checkbox"/>	<input type="checkbox"/>						
7.5.	Restmengen oder leere Gefahrstoffgebinde werden sicher gelagert und sachgerecht entsorgt	<input type="checkbox"/>	<input type="checkbox"/>						
8.	Aufbewahrung und Lagerung²⁾								
8.1.	Die Lagerung ist übersichtlich	<input type="checkbox"/>	<input type="checkbox"/>						
8.2.	Eindeutige Lagerorte sind vorhanden (2)	<input type="checkbox"/>	<input type="checkbox"/>						
8.3.	Keine Aufbewahrung und Lagerung in Lebensmittelbehältnissen	<input type="checkbox"/>	<input type="checkbox"/>						
8.4.	Keine Aufbewahrung und Lagerung neben Arznei-, Futter- und Lebensmitteln	<input type="checkbox"/>	<input type="checkbox"/>						
8.5.	Staubarme bzw. flüssigkeitsdichte (Dampfdichte) Lagerung	<input type="checkbox"/>	<input type="checkbox"/>						
9.	Physikalisch-chemische Gefährdungen								
9.1.	Bei Tätigkeiten mit Stoffen, die zu Brand- und	<input type="checkbox"/>	<input type="checkbox"/>						

Firmenlogo	Erfassung der erforderlichen Schutzmaßnahmen Allgemeine und zusätzliche Schutzmaßnahmen nach §§ 8, 9 und 11 GefStoffV - Gefährdungsbeurteilung - Dokumentation -	Datum: Betrieb:
------------	--	--------------------

Tätigkeit/Personen:

Gefahrstoffe

Anforderung nach §§ 8, 9 und 11 GefStoffV

Nr.	Maßnahmen	Erfüllt		Schutzmaßnahmen (technisch-organisatorisch-persönlich)	Beratungsbedarf	Realisierung		Wirksamkeit	
		ja	nein			Bis wann	durch	wirksam	wann
	Explosionsgefahren führen können, wurden weitere Maßnahmen getroffen								
9.2.	Bei Tätigkeiten mit Stoffen, deren physikalisch-chemische Eigenschaften zu weiteren Gefährdungen führen können, wurden weitere Maßnahmen getroffen	<input type="checkbox"/>	<input type="checkbox"/>						

Bemerkungen	1) Bezieht sich auf alle Tätigkeiten mit erhöhter Staubentwicklung, spritzenden Arbeitsverfahren oder sonstigen Arbeitsplätzen mit erhöhter Stoffbelastung. 2) Bezieht sich auf alle chemischen Arbeitsstoffe.
-------------	---

Erfassung der erforderlichen Schutzmaßnahmen nach §§ 8,9 und 11 GefStoffV

Anmerkungen zu:

Spalte 2: „Maßnahmen“

[Firmenlogo]	Gefahrstoffe – Gefährdungsbeurteilung (Beiblatt zu Gefährdungsbeurteilung - Dokumentation)	Abschnitt 2.1
--------------	--	------------------

Aus den Inhalten der Gefahrstoffverordnung wurden die erforderlichen Maßnahmen nach den Schutzstufen zusammengestellt. Ist in dem entsprechenden Arbeitsbereich die Schutzstufe 2 anzuwenden, so dient diese Spalte als Checkliste für die geforderten Schutzmaßnahmen. Die vorliegende Checkliste nach der Schutzstufe 2 *plus* beinhaltet darüber hinaus die Forderungen zu dermalen und physisch-chemischen Gefährdungen.

Spalte 3: „Erfüllt“

Ist die Maßnahme noch nicht umgesetzt, besteht eine potentielle Gefährdung/ Belastung für die Mitarbeiter, die durch entsprechende Schutzmaßnahmen (technisch-organisatorisch-persönlich) zu beseitigen sind.

Spalte 4: „Schutzmaßnahmen“

Wurde in Spalte 3 „nein“ eingetragen: Ist in Spalte 4 die betreffende Maßnahme aus der Spalte 2 als umzusetzende Schutzmaßnahme zu konkretisieren. Wurde in Spalte 3 „ja“ eingetragen: Können in Spalte 4 auch bereits realisierte Maßnahmen kommentiert werden, ggf. auch auf vorhandene Unterlagen verwiesen werden.

Spalte 5:

Beratungsbedarf kann nötig sein, wenn Unsicherheiten bei der Erfüllung (Spalte 2) oder Bewertung (Spalte 3) der Gefährdungen oder bei der Maßnahmenfestlegung (Spalte 4) bestehen.

Spalte 6:

Die Realisierung der Maßnahmen wird von der verantwortlichen Führungskraft kontrolliert.

Spalte 7:

Wirksamkeit von Maßnahmen z. B. bei Begehungen, Audits, Sicherheitsbegehungen kontrollieren.