Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

STONE GUARD BLACK
1000 ml Art.: 6610 6010, Art.: 6614 6010

1.2 Relevant identified uses of the substance or mixture and uses advised against
Relevant identified uses of the substance or mixture:
Underfloor protection
Sector of use [SU]:
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet
GB

Theo Förch GmbH & Co. KG, Theo-Förch-Str. 11 - 15, 74196 Neuenstadt, Germany
Phone:07139/95-0, Fax:07139/95-199
info@foerch.de, www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number
Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:
+49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Flam. Liq.	2	H225-Highly flammable liquid and vapour.
Skin Irrit.	2	H315-Causes skin irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

2.2 Label elements
Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H225-Highly flammable liquid and vapour. H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves.
P312-Call a POISON CENTRE / doctor if you feel unwell.
P403+P233-Store in a well-ventilated place. Keep container tightly closed.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
Hazardous to drinking water, on escape of even small quantities.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	---
EINECS, ELINCS, NLP	921-024-6 (REACH-IT List-No.)
CAS	---
content %	30-50
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411

Xylene (mixture of isomers)	**Substance for which an EU exposure limit value applies.**
Registration number (REACH)	---
Index	601-022-00-9
EINECS, ELINCS, NLP	215-535-7
CAS	1330-20-7
content %	1-<12,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Skin Irrit. 2, H315

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.
Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Call doctor immediately - have Data Sheet available.
Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
The following may occur:
Headaches
Dizziness
Effects/damages the central nervous system
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
Oxides of carbon
Toxic gases
Explosive vapour/air or gas/air mixtures.
Dangerous vapours heavier than air.
In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.
Ensure sufficient supply of air.
Avoid inhalation, and contact with eyes or skin.
If applicable, caution - risk of slipping.

6.2 Environmental precautions
If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up
Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections
For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations
Avoid aerosol formation.
Ensure good ventilation.
If applicable, suction measures at the workstation or on the processing machine necessary.
Keep away from sources of ignition - Do not smoke.
Take precautions against electrostatic charges.
Avoid contact with eyes or skin.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace
General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities
Keep out of access to unauthorised individuals.
Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Observe special storage conditions.
Store in a well ventilated place.
Store cool.
Store in a dry place.

7.3 Specific end use(s)
No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters
Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
600 mg/m3

GB **Chemical Name**	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Content %:30-50
WEL-TWA: 600 mg/m3	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-187 S (551 174)	
BMGV: ---	Other information: (WEL acc. to RCP-method, EH40)	

GB **Chemical Name**	Xylene (mixture of isomers)	Content %:1-<12,5
WEL-TWA: 50 ppm (220 mg/m3) (WEL), 50 ppm (221 mg/m3) (EU)	WEL-STEL: 100 ppm (441 mg/m3 (WEL), 100 ppm (442 mg/m3) (EU)	---
Monitoring procedures:	- Compur - KITA-143 SA (550 325) - Compur - KITA-143 SB (505 998) - Draeger - Xylene 10/a (67 33 161)	

-	MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 47-1 (2004)
BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV)	Other information: Sk (WEL)

GB Chemical Name	Calcium carbonate	Content %:>=
WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust)	WEL-STEL: ---	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	149	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	

Xylene (mixture of isomers)

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,327	mg/l	
	Environment - sediment, freshwater		PNEC	12,46	mg/kg	
	Environment - soil		PNEC	2,31	mg/kg	
	Environment - marine		PNEC	0,327	mg/l	
	Environment - sediment, marine		PNEC	12,46	mg/kg	
	Environment - sewage treatment plant		PNEC	6,58	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m3	

Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg	

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
Applies only if maximum permissible exposure values are listed here.
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
These are specified by e.g. BS EN 14042.
BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
Solvent resistant protective gloves (EN 374).
If applicable
Protective Viton® / fluoroelastomer gloves (EN 374)
Protective nitrile gloves (EN 374)
Minimum layer thickness in mm:
0,4
Permeation time (penetration time) in minutes:
> 480
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
The recommended maximum wearing time is 50% of breakthrough time.
Protective hand cream recommended.

Skin protection - Other:
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
If OES or MEL is exceeded.
Filter A (EN 14387), code colour brown
At high concentrations:
Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
Not applicable

Additional information on hand protection - No tests have been performed.
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
Selection of materials derived from glove manufacturer's indications.
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Black
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	98 °C
Flash point:	2 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	0,6 Vol-% (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)
Upper explosive limit:	7 Vol-% (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,055 g/ml
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	200 °C (Ignition temperature)
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	7500-10500 mPas
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity
The product has not been tested.

10.2 Chemical stability
Stable with proper storage and handling.

10.3 Possibility of hazardous reactions
Possible build up of explosive/highly flammable vapour/air mixture.

10.4 Conditions to avoid
See also section 7.
Heating, open flame, ignition sources

10.5 Incompatible materials
See also section 7.
Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products
See also section 5.2
No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects
Possibly more information on health effects, see Section 2.1 (classification).

STONE GUARD BLACK
1000 ml Art.: 6610 6010, Art.: 6614 6010

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>25,2	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant (Analogous conclusion)
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Analogous conclusion, Negative
Carcinogenicity:						Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative
Aspiration hazard:						Yes

Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Not irritant (respiratory tract).

Xylene (mixture of isomers)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2840	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>1700	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	21,7	mg/l/4h	Rat		Vapours, Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit		Irritant
Serious eye damage/irritation:				Rabbit		Slightly irritant
Respiratory or skin sensitisation:					(Patch-Test)	Negative
Symptoms:						breathing difficulties, drying of the skin., drowsiness, unconsciousness, burning of the membranes of the nose and throat, vomiting, skin afflictions, heart/circulatory disorders, coughing, headaches, drowsiness, dizziness, nausea

Calcium carbonate

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:						No (skin contact)
Germ cell mutagenicity:					in vitro	Negative

Carcinogenicity:						Negative, administered as Ca-lactate
Reproductive toxicity:						Negative, administered as Ca-carbonate

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

STONE GUARD BLACK
1000 ml Art.: 6610 6010, Art.: 6614 6010

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:	AOX						Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	NOELR	28d	2,04	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LL50	96h	11,4	mg/l	Salmo gairdneri	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	NOELR	48h	2,1	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	81	%			Analogous conclusion
12.3. Bioaccumulative potential:	BCF		242-253				
12.4. Mobility in soil:							Adsorption in ground., Product is slightly volatile.

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	AOX		0	%			

Xylene (mixture of isomers)							
Toxicity / effect	**Endpoint**	**Time**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
12.1. Toxicity to fish:	LC50	96h	86	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	8,2	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	24h	75,5	mg/l	Daphnia magna		
12.1. Toxicity to algae:	IC50	72h	10	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		>3				
12.3. Bioaccumulative potential:	BCF		0,6-15				

Calcium carbonate							
Toxicity / effect	**Endpoint**	**Time**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:					Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Negative
Water solubility:			0,014	g/l			

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:
The waste codes are recommendations based on the scheduled use of this product.
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances
Recommendation:
Sewage disposal shall be discouraged.
Pay attention to local and national official regulations.
E.g. dispose at suitable refuse site.
E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.
Empty container completely.
Uncontaminated packaging can be recycled.
Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: 1139

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
UN 1139 COATING SOLUTION



14.3. Transport hazard class(es): 3
14.4. Packing group: II
Classification code: F1
LQ: 5 L
14.5. Environmental hazards: environmentally hazardous
Tunnel restriction code: D/E

Transport by sea (IMDG-code)

14.2. UN proper shipping name:
COATING SOLUTION (NAPHTHA (PETROLEUM))



14.3. Transport hazard class(es): 3
14.4. Packing group: II
EmS: F-E, S-E
Marine Pollutant: Yes
14.5. Environmental hazards: environmentally hazardous

Transport by air (IATA)

14.2. UN proper shipping name:
Coating solution



14.3. Transport hazard class(es): 3
14.4. Packing group: II
14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
All persons involved in transporting must observe safety regulations.
Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
Minimum amount regulations have not been taken into account.
Danger code and packing code on request.
Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): ~ 51,1 %

REGULATION (EC) No 648/2004

n.a.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.
A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 8
Employee training in handling dangerous goods is required.
These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Skin Irrit. 2, H315	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Flam. Liq. — Flammable liquid
Skin Irrit. — Skin irritation
STOT SE — Specific target organ toxicity - single exposure - narcotic effects
Aquatic Chronic — Hazardous to the aquatic environment - chronic
Asp. Tox. — Aspiration hazard
Acute Tox. — Acute toxicity - inhalation
Acute Tox. — Acute toxicity - dermal

Förch France SAS
ZAE Marchais Renard/Aubigny
77950 Montereau-sur-le-Jard
FRANKREICH
Tel. +33 1 64144848
Fax +33 1 64144849
E-Mail: info@forch.fr
Internet: www.forch.fr

Förch SAS
17 rue de Marbourg
9764 MARNACH
LUXEMBURG
Tel. +352 269 03267
Fax +352 269 03368
E-Mail: info@forch.fr
Internet: www.forch.fr

S.C. Foerch S.R.L.
Str. Zizinului 110
500407 Brasov
RUMÄNIEN
Tel. +40 368 408192
Fax +40 368 408193
E-Mail: info@foerch.ro
Internet: www.foerch.ro

Fцrch A/S
Hagemannsvej 3
8600 SILKEBORG
DДNEMARK
Tel. +45 86 823711
Fax +45 86 800617
E-Mail: info@foerch.dk
Internet: www.foerch.dk

Foerch AG
Netzibodenstrasse 23D
4133 Pratteln
SCHWEIZ
Tel. +41 61 8262030
Fax +41 61 8262039
E-Mail: info@foerch.ch
Internet: www.foerch.ch

Foerch Bulgaria EOOD
22 Parva Balgarska Armiya Str.
1220 Sofia, Bulgarien
Tel: 00359 2 981 2841
Fax: 00359 882 10 30 86
E-Mail: info@foerch.bg

Förch d.o.o.
Buzinska cesta 58
10010 Zagreb
KROATIEN
Tel. +385 1 2912900
Fax +385 1 2912901
E-Mail: info@foerch.hr
internet: www.foerch.hr

Theo Förch GmbH
Röcklbrunnstraße 39A
5020 Salzburg
ÖSTERREICH
Tel. +43 662 875574-0
Fax +43 662 878677-21
Verkauf Tel. +43 662 875574-900
Verkauf Fax +43 662 875574-30
E-Mail: info@foerch.at
Internet: www.foerch.at

Förch Componentes para Taller S.L.
Camino de San Antón, S/N
18102 Ambroz (Granada)
SPANIEN
Tel. +34 958 40 17 76
Fax +34 958 40 17 87
E-Mail: info@forch.es
Internet: www.forch.es

Lhomme Tools & Fasteners
SEINHUISSTRAAT 5 B4
POORT 0331
3600 Genk
BELGIEN
Tel +32 89 71 66 61
Fax +32 89 71 59 27
E-Mail: info@lhommetools.be
Internet: www.lhommetools.be

Ziebe Limited
82 Westcott Venture Park
HP18 0XB Westcott, Aylesbury, Bucks
GROSSBRITANNIEN
Tel +44 12 96 65 52 82
Fax +44 12 96 65 19 47
E-Mail: sales-dept@ziebe.co.uk
Internet: www.ziebe.co.uk

Foermi Handelshaus LLC
Dimitrovskoe Autostrasse
Building 107/18
127247 Moscow
RUSSISCHE FOEDERATION
Tel. 7-495 657 99 57
Fax 7-495 485 87 98
E-Mail: foermi.moscow@foerch.ru
Internet: www.forch.ru

Förch Polska Sp. z o.o.
43-392 MIĘDZYRZECZE GÓRNE 379
POLEN
k/ Bielska-Białej
Tel. +48 33 8156000
Fax +48 33 8158548
E-Mail: info@forch.pl
Internet: www.forch.pl

Vardalis SM P.C.
62, ETHNIKIS ANTISTASIS STR.
57007 CHALKIDONA/THESSALONIKI
GRIECHENLAND
Tel +30 23 91 02 12 22
Fax +30 23 91 02 12 23
E-Mail: info@forch.gr
Internet: www.foerch.com

Förch Kereskedelmi Kft
Börgöndi út 14
8000 Székesfehérvár
UNGARN
Tel. +36 22 348348
Fax +36 22 348355
E-Mail: info@foerch.hu
Internet: www.foerch.hu

Förch S.R.L.
VIA GALVANI 40 C
39100 BOLZANO
ITALIEN
Tel. +39 0471 204330
Fax +39 0471 204290
E-Mail: info@forch.it
Internet: www.forch.it

Förch Nederland BV
Demmersweg 18
7556 BN Hengelo
NIEDERLANDE
Tel. +31 85 7732420
E-Mail: info@foerch.nl
Internet: www.foerch.nl

Bilanaust Ehf.
Dvergshofda 2
110 Reykjavik
ISLAND
Tel. +354 535 9000
Fax. +354 535 9097
E-Mail: bilanaust@bilanaust.is
Internet: www.bilanaust.is

Förch Slovensko s.r.o.
Rosinská cesta 12
010 08 ŽILINA
SLOWAKEI
Tel +421 41 5002454
Fax +421 41 5002455
E-Mail: info@forch.sk
Internet: www.forch.sk

Normteknik i Sverige AB
Brännarevägen 1
151 55 Södertälje
SCHWEDEN
Tel. +46 8 55 08 92 64
Fax +46 8 55 08 90 62
E-Mail: info@foerch.se
Internet: www.foerch.se

Förch s.r.o.
Dopravní 1314/1
10400 PRAHA 10 – Uhříněves
TSCHECHIEN
Tel. +420 271 001 984-9
Fax +420 271 001 994-5
E-Mail: info@foerch.cz
Internet: www.foerch.cz

Förch d.o.o.
LJUBLJANSKA CESTA 51A
1236 TRZIN
SLOWENIEN
Tel. +386 1 2442490
Fax +386 1 2442492
E-Mail: info@foerch.si
Internet: www.foerch.si

Forch Australia
2 Forward Street
GNANGARA WA 6077
Tel +61 (08) 9303 9113
Fax: +61 (08) 9303 9114
Emergency telephone: +614 13 550 330
Email : sales@forch.com.au
Internet: www.forch.com.au

Förch Portugal Lda
Rua REPUBLICA DA BOLIVIA No. 69, 1 ESQ
1500-544 Lisboa
PORTUGAL
Tel. +351 917314442
Fax +351 253339576
E-Mail: info@forch.pt
Internet: www.forch.pt

Trigers SIA
Straupes Street IELA 3
1073 Riga
LETTLAND
Tel +371 6 7 90 25 15
Fax +371 67 90 24 96
E-Mail: trigers@trigers.lv
Internet: www.trigers.lv

Förch Otomotiv Inþ. ve San. Ürünleri
Haramidere Mevkii Beysan Sanayi
Sitesi Birlik Caddesi No:6/3
34524 Beylikdüzü / Istanbul
Türkei
Tel. +90 (0)212 422 8744
Fax +90 (0)212 422 8788
E-Mail: info@forch.com.tr
Internet: www.forch.com.tr

Any abbreviations and acronyms used in this document:

AC Article Categories
acc., acc. to according, according to
ACGIH American Conference of Governmental Industrial Hygienists
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOEL Acceptable Operator Exposure Level
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
BMGV Biological monitoring guidance value (EH40, UK)
BOD Biochemical oxygen demand
BSEF Bromine Science and Environmental Forum
bw body weight
CAS Chemical Abstracts Service
CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC Collaborative International Pesticides Analytical Council
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
COD Chemical oxygen demand
CTFA Cosmetic, Toiletry, and Fragrance Association
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
DT50 Dwell Time - 50% reduction of start concentration
DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ERC Environmental Release Categories
ES Exposure scenario
etc. et cetera
EU European Union
EWC European Waste Catalogue
Fax. Fax number
gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
HET-CAM Hen's Egg Test - Chorionallantoic Membrane
HGWP Halocarbon Global Warming Potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC Intermediate Bulk Container
IBC (Code) International Bulk Chemical (Code)
IC Inhibitory concentration
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform ChemicaL Information Database
LC lethal concentration
LC50 lethal concentration 50 percent kill
LCLo lowest published lethal concentration
LD Lethal Dose of a chemical
LD50 Lethal Dose, 50% kill
LDLo Lethal Dose Low
LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAEC No Observed Adverse Effective Concentration
NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.
These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.

Nummer:

Datum:

Bearbeiter:

Verantwortlicher:

Arbeitsbereich:

Arbeitsplatz / Tätigkeit:

BETRIEBSANWEISUNG
gem. § 14 GefStoffV.

Betrieb:

GEFAHRSTOFFBEZEICHNUNG

Leichtentzündliche umweltgefährdende Produkte

Es können die folgenden gefährlichen Stoffe enthalten sein:
Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cycloalkane, <5% n-Hexan, Xylol, Naphtha (Erdöl), Ethanol, Ethylacetat, Toluol, Trizinkbis(orthophosphat), Zinkoxid, Mesitylen, 1,2,4-Trimethylbenzol,

GEFAHREN FÜR MENSCH UND UMWELT







Gefahr

Diese Betriebsanweisung gilt für die folgenden Produkte:
6610 6010 - STONE GUARD BLACK
1000 ml

GHS-EINSTUFUNG NACH VERORDNUNG (EG) 1272/2008

Flüssigkeit und Dampf leicht entzündbar / entzündbar. Es können auftreten:
Verursacht Hautreizungen. Verursacht schwere Augenreizungen. Kann die Atemwege reizen.
Kann Schläfrigkeit und Benommenheit verursachen.
Giftig für Wasserorganismen, mit langfristiger Wirkung.

Komplexe Kombination von Kohlenwasserstoffen. Die beinhalteten Lösemittel können über die Atemwege aufgenommen werden. Beim Einatmen hoher Lösungsmittelkonzentrationen können Reizungen an den Augen, Atemwegen und Schleimhäuten auftreten. Als Symptome können Rausch, Schwindel, Bewegungsstörungen, Schläfrigkeit, Übelkeit, Appetitlosigkeit, Erbrechen auftreten. Daneben wirken sie entfettend auf die Haut. Es können Stoffe enthalten sein, die eine allergische Reaktione auslössen können.

SCHUTZMASSNAHMEN UND VERHALTENSREGELN







Hygienevorschriften:
Nach Produktentnahme darauf achten, dass an der Außenverpackung keine Produktreste anhaften. Berührung mit den Augen, der Haut und der Kleidung vermeiden. Vor den Pausen und bei Arbeitsende Hände gründlich waschen. Vor dem Arbeitsbeginn und nach Pausen Hautschutzsalbe auftragen. Langärmelige Arbeitsschutzkleidung verwenden. Produkt sofort mit geeignetem Reinigungsmittel von der Haut entfernen. Keine Lösungsmittel verwenden. Das Essen, Trinken, Rauchen, sowie die Aufbewahrung von Lebensmitteln im Arbeitsraum ist verboten. Während des Umgangs mit dem Produkt keine Nahrungs- und Genussmittel aufnehmen.

Technische und organisatorische Schutzmaßnahmen zur Verhütung einer Exposition:
Bei der Anwendung des Produktes für gute Be- und Entlüftung sorgen.
Auf Sauberkeit am Arbeitsplatz achten. Verspritzen vermeiden.

Persönliche Schutzausrüstung:
Schutzbrille dichtschließend mit Seitenteilen verwenden.
Chemikalienbeständige Schutzhandschuhe (nach DIN EN 374) aus geeignetem Material wie z. B. Gummi, PVC, Neopren, Latex, oder Butylkautschuk tragen.

Bei Auftreten von Dämpfen oder unzureichender Belüftung oder bei Überschreitung des Arbeitsplatzgrenzwertes Atemschutzmaske benutzen. Weitere Angaben zu der geeigneten Schutzausrüstung finden Sie unter Punkt 8 im Sicherheitsdatenblatt des jeweiligen Produktes.

Beschränkungen für Beschäftigte:
Der Umgang mit Gefahrstoffen ist für Jugendliche nur erlaubt, wenn es zur Erreichung des Ausbildungsziels erforderlich ist. Dabei müssen die Jugendlichen mindestens 16 Jahre alt sein und durch einen Fachkundigen beaufsichtigt werden.

VERHALTEN IM GEFAHRFALL



NOTRUF:

Geeignete und ungeeignete Löschmittel:
Geeignete Löschmittel sind Wassersprühstrahl und Feuerlöscher mit Pulver für die Brandklassen A, B, C, sowie Kohlendioxidlöscher. Brände nicht mit Wasservollstrahl löschen.

Aufsaug- und Bindemittel, Neutralisationsmittel:
Verschüttete Reste mit nicht brennbarem Bindemittel aufnehmen und sachgerecht entsorgen.

Zusätzliche technische Schutzmaßnahmen und persönliche Schutzausrüstung:
Alle Zündquellen beseitigen. Hautkontakt und Inhalation des Stoffes vermeiden. Bei Brand oder starkem Erwärmen ist die Bildung von explosionsfähigen Dampf- / Luftgemischen sowie giftigen Zersetzungsprodukten möglich. Chemikalienbeständige Schutzkleidung verwenden.
Verschmutzte Kleidung sofort wechseln und erst nach deren Reinigung wieder benutzen.
Bei Bränden den gefährdeten Bereich räumen, betroffene Umgebung warnen.
Persönliche Schutzausrüstung verwenden.

Notwendige Maßnahmen gegen Umweltgefährdungen:
Löschwasser nicht in den Boden, das Grundwasser oder die Kanalisation gelangen lassen.

Aushang Flucht- und Rettungswegpläne:

Aushang Alarmpläne:

ERSTE HILFE



NOTRUF:

Augenkontakt:
Auge unter Schutz des unverletzten Auges 10 Minuten unter fließendem Wasser bei weit gespreizten Lidern spülen. Für ärztliche Behandlung sorgen.

Hautkontakt:
Benetzte Kleidung entfernen, dabei Selbstschutz beachten. Betroffene Hautpartien sofort gründlich unter fließendem Wasser mit Seife reinigen. Nach großflächigem Kontakt oder bei anhaltenden Reizungen für ärztliche Behandlung sorgen.

Einatmen:
Verletzten unter Selbstschutz aus dem Gefahrenbereich an die frische Luft bringen.
Verletzten ruhig lagern, vor Unterkühlung schützen. Bei Bewusstlosigkeit und vorhandener Atmung stabile Seitenlage. Für ärztliche Behandlung sorgen.

Verschlucken:
Nach versehentlicher Aufnahme von den oben genannten Produkten Mund ausspülen, Flüssigkeit wieder ausspucken. Sofort - bei erhaltenem Bewusstsein - reichlich Flüssigkeit (Wasser) trinken lassen. Für ärztliche Behandlung sorgen.

Verbrennungen:
Verbrannte Hautflächen mit fließendem Wasser kühlen. Für ärztliche Behandlung sorgen.

Ersthelfer:

Erste Hilfe Einrichtungen:

SACHGERECHTE ENTSORGUNG

Mit Tüchern oder Universalbindemittel gründlich aufnehmen und Boden reinigen. Dabei geeignete Schutzausrüstung verwenden. Gebinde restlos entleeren und H inweis auf der Verpackung beachten.

Entsorgungsbehälter / Sammelstelle

Aufsaugmittel:

Reinigungsmittel:

Erstellt am:

Unterschrift Verantwortlicher:

Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

STONE GUARD BLACK 1000 ml
Art.: 6610 6010, Art.: 6614 6010

1.2 Relevant identified uses of the substance or mixture and uses advised against
Relevant identified uses of the substance or mixture:
Underfloor protection
Sector of use [SU]:
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet
Theo Förch GmbH & Co. KG, Theo-Förch-Str. 11 - 15, D-74196 Neuenstadt
Telephone 07139/95-0, Fax 07139/95-199
E-Mail info@foerch.de Internet www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

1.4 Emergency telephone
Advisory office in case of poisoning:

Telephone number of the company in case of emergencies:
Tel.: +49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)
Not determined
2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)
F, Highly flammable, R11
Xi, Irritant, R38
N, Dangerous for the environment, R51-53
R67
2.2 Label elements
2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)
Not determined
2.2.2 Labeling according to Directives 67/548/EEC and 1999/45/EC (including amendments)



Symbols: F/Xi/N
Indications of danger:
Highly flammable
Irritant
Dangerous for the environment

R-phrases:
38 Irritating to skin.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67 Vapours may cause drowsiness and dizziness.
S-phrases:
(2) Keep out of the reach of children.
9 Keep container in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.
23 Do not breathe vapour.
29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
(46) If swallowed, seek medical advice immediately and show this container or label.
61 Avoid release to the environment. Refer to special instructions/Safety data sheets.
Additions: n.a.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.
The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.
Hazardous to drinking water, on escape of even small quantities.

REGULATION (EC) No 648/2004

n.a.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	921-024-6 (REACH-IT List-No.)
CAS	CAS ---
content %	30-50
Classification according to Directive 67/548/EEC	Highly flammable, F, R11 Irritant, Xi, R38 Dangerous for the environment, N, R51 Dangerous for the environment, R53 Harmful, Xn, R65 R67
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411

Xylene (mixture of isomers)	Substance for which an EU exposure limit value applies.
Registration number (REACH)	--
Index	601-022-00-9
EINECS, ELINCS, NLP	215-535-7
CAS	CAS 1330-20-7
content %	1-<12,5
Classification according to Directive 67/548/EEC	Flammable, R10 Harmful, Xn, R20/21 Irritant, Xi, R38
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Skin Irrit. 2, H315

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 31.08.2011 / 0011
Replaces revision of / Version: 19.01.2011 / 0010
Valid from: 31.08.2011
PDF print date: 13.07.2012
STONE GUARD BLACK 1000 ml Art.: 6610 6010

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.
Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Call doctor immediately - have Data Sheet available.
Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
The following may occur:
Headaches
Dizziness
Effects/damages the central nervous system

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
Oxides of carbon
Toxic gases
Explosive vapour/air mixture
Dangerous vapours heavier than air.
In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.
Ensure sufficient supply of air.
Avoid inhalation, and contact with eyes or skin.
If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up
Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections
For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations
Avoid aerosol formation.
Ensure good ventilation.
If applicable, suction measures at the workstation or on the processing machine necessary.
Keep away from sources of ignition - Do not smoke.
Take precautions against electrostatic charges.
Avoid contact with eyes or skin.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace
General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities
Keep out of access to unauthorised individuals.
Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").
Store in a well ventilated place.
Store cool
Store in a dry place.

7.3 Specific end use(s)
No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters
Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
800 mg/m3

GB **Chemical Name**	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	Content %:30-50
WEL-TWA: 800 mg/m3	WEL-STEL: ---	---
BMGV: ---	Other information: ---	

GB **Chemical Name**	Xylene (mixture of isomers)	Content %:1-<12,5
WEL-TWA: 50 ppm (220 mg/m3) (WEL), 50 ppm (221 mg/m3) (EC)	WEL-STEL: 100 ppm (441 mg/m3 (WEL), 100 ppm (442 mg/m3) (EC)	---
BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV)	Other information: Sk (WEL)	

GB **Chemical Name**	Calcium carbonate	Content %:>=
WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust)	WEL-STEL: ---	---
BMGV: ---	Other information: ---	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane						
Area of application	**Exposure route / Environmental compartment**	**Effect on health**	**Descriptor**	**Value**	**Unit**	**Note**
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/day	

8.2 Exposure controls
8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
Solvent resistant protective gloves (EN 374).
If applicable
Protective Viton gloves (EN 374)
Protective nitrile gloves (EN 374)
Protective hand cream recommended.

Skin protection - Other:
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:
If OES or MEL is exceeded.
Filter A (EN 14387), code colour brown
At high concentrations:
Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
Not applicable

Additional information on hand protection - No tests have been performed.
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
Selection of materials derived from glove manufacturer's indications.
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Black
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	98 °C
Flash point:	2 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	0,6 Vol-% (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane)
Upper explosive limit:	7 Vol-% (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane)
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,055 g/ml
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	200 °C (Ignition temperature)
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	7500-10500 mPas
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity
The product has not been tested.

10.2 Chemical stability
Stable with proper storage and handling.

10.3 Possibility of hazardous reactions
Possible build up of explosive/highly flammable vapour/air mixture.

10.4 Conditions to avoid
See also section 7.
Heating, open flame, ignition sources

10.5 Incompatible materials
See also section 7.
Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products
See also section 5.2
No decomposition when used as directed.

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

STONE GUARD BLACK 1000 ml Art.: 6610 6010						
Toxicity/effect	**Endpoint**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**

Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Respiratory tract irritation:						n.d.a.
Repeated dose toxicity:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2920	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>25,2	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Acute toxicity, by inhalation:	LC50	>25,2	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant (Analogous conclusion)
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Analogous conclusion, No (inhalation and skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Analogous conclusion, Negative
Carcinogenicity:						Analogous conclusion, Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative
Aspiration hazard:						Yes
Respiratory tract irritation:						Not irritant
Symptoms:						dizziness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Xylene (mixture of isomers)

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2840	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	2000	mg/kg	Rabbit		

Acute toxicity, by inhalation:	LC50	21,7	mg/l/4h	Rat		Does not conform with EU classification., References
Skin corrosion/irritation:				Rabbit		Irritant
Serious eye damage/irritation:				Rabbit		Slightly irritant
Respiratory or skin sensitisation:					(Patch-Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						breathing difficulties, drying of the skin., dizziness, unconsciousness, burning of the membranes of the nose and throat, vomiting, skin afflictions, heart/circulatory disorders, coughing, headaches, drowsiness, dizziness, nausea

Calcium carbonate

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Respiratory or skin sensitisation:						No indications of such an effect.
Other information:						References, Harmless, is approved as additive for food (E170).

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

STONE GUARD BLACK 1000 ml
Art.: 6610 6010

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							n.d.a.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.
Other information:	AOX						Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	11,4	mg/l	(Oncorhynchus mykiss)	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to daphnia:	EC50	48h	3	mg/l	(Daphnia magna)	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

Toxicity to daphnia:	NOEC/NOEL	21d	1	mg/l	(Daphnia magna)	OECD 211 (Daphnia magna Reproduction Test)	
Toxicity to algae:	EC50	72h	30	mg/l	(Pseudokirchneriella subcapitata)	OECD 201 (Alga, Growth Inhibition Test)	
Persistence and degradability:		28d	81	%			Analogous conclusion
Bioaccumulative potential:							Concentration in organisms possible.
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Xylene (mixture of isomers)							
Toxicity/effect	**Endpoint**	**Time**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
Toxicity to fish:	LC50	96h	8,2	mg/l	(Oncorhynchus mykiss)		
Toxicity to fish:	LC50	96h	86	mg/l	(Leuciscus idus)		
Toxicity to daphnia:	EC50	24h	75,5	mg/l	(Daphnia magna)		
Toxicity to algae:	IC50	72h	10	mg/l			
Persistence and degradability:							Readily biodegradable
Bioaccumulative potential:	Log Pow		>3				
Bioaccumulative potential:	BCF		0,6-15				

Calcium carbonate							
Toxicity/effect	**Endpoint**	**Time**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
Toxicity to fish:	LC50	96h	>10000	mg/l			
Toxicity to daphnia:	EC50	48h	>1000	mg/l			
Toxicity to algae:	IC50	72h	>200	mg/l			
Persistence and degradability:							Not relevant for inorganic substances.
Bioaccumulative potential:	Log Pow		<1				Bioaccumulation is unlikely (LogPow < 1).
Water solubility:			14-16	mg/l			20°C

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:
The waste codes are recommendations based on the scheduled use of this product.
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)
08 04 09 waste adhesives and sealants containing organic solvents or other dangerous substances
Recommendation:
Pay attention to local and national official regulations
E.g. dispose at suitable refuse site.
E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations
Empty container completely.
Uncontaminated packaging can be recycled.
Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

UN number: 1139

Transport by road/by rail (ADR/RID)




UN proper shipping name:
UN 1139 COATING SOLUTION (SPECIAL PROVISION 640D)

Transport hazard class(es):	3
Packing group:	II
Classification code:	F1
LQ (ADR 2011):	5 L
LQ (ADR 2009):	6
Environmental hazards:	environmentally hazardous
Tunnel restriction code:	D/E

Transport by sea (IMDG-code)




UN proper shipping name:
COATING SOLUTION (NAPHTHA (PETROLEUM))

Transport hazard class(es):	3
Packing group:	II
EmS:	F-E, S-E
Marine Pollutant:	Yes
Environmental hazards:	environmentally hazardous

Transport by air (IATA)



UN proper shipping name:
Coating solution

Transport hazard class(es):	3
Packing group:	II
Environmental hazards:	Not applicable

Special precautions for user

Persons employed in transporting dangerous goods must be trained.
All persons involved in transporting must observe safety regulations.
Precautions must be taken to prevent damage.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
Minimum amount regulations have not been taken into account.
Danger code and packing code on request.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.
Observe restrictions: Yes
Comply with trade association/occupational health regulations.
Observe youth employment law (German regulation).
VOC 1999/13/EC ~ 51,1%

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.
A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

These details refer to the product as it is delivered.
Revised sections: 3, 8, 9, 10, 12
The following statements are the indicated R-phrases / H-phrases and classification codes (GHS/CLP) for the ingredients (listed in Section 3).
11 Highly flammable.
20/21 Harmful by inhalation and in contact with skin.
38 Irritating to skin.
51 Toxic to aquatic organisms.
53 May cause long-term adverse effects in the aquatic environment.
65 Harmful: may cause lung damage if swallowed.
67 Vapours may cause drowsiness and dizziness.
10 Flammable.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.

H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Flam. Liq.-Flammable liquid
Asp. Tox.-Aspiration hazard
Skin Irrit.-Skin irritation
STOT SE-Specific target organ toxicity - single exposure - narcotic effects
Aquatic Chronic-Hazardous to the aquatic environment - chronic
Acute Tox.-Acute toxicity - inhalation
Acute Tox.-Acute toxicity - dermal

Förch France SA
ZAE Le Marchais Renard
Aubigny
77950 Montereau-sur-le-Jard
FRANKREICH
Tel. +33 1 64144848
Fax +33 1 64144849
E-Mail info@forch.fr
Internet www.forch.fr

Förch SNC
17 rue de Marbourg
9764 MARNACH
LUXEMBURG
Tel. +352 269 03267
Fax +352 269 03368
E-Mail info@forch.fr
Internet www.forch.fr

S.C. Foerch S.R.L.
Str. Zizinului 110
500407 Brasov
RUMÄNIEN
Tel. +40 368 408192
Fax +40 368 408193
E-Mail info@foerch.ro
Internet www.foerch.ro

Förch A/S
Hagemannsvej 3
8600 SILKEBORG
DÄNEMARK
Tel. +45 86 823711
Fax +45 86 800617
E-Mail info@foerch.dk
Internet www.foerch.dk

Förch AG
Netzibodenstrasse 23D
4133 Pratteln
SCHWEIZ
Tel. +41 61 8262030
Fax +41 61 8262039
E-Mail info@foerch.ch
Internet www.foerch.ch

Förch d.o.o.
Velika Cesta 34, Odra
10020 ZAGREB
KROATIEN
Tel. +385 1 2912900
Fax +385 1 2912901
E-Mail info@foerch.hr
internet www.foerch.hr

Theo Förch GmbH
Röcklbrunnstraße 39A
5020 Salzburg
ÖSTERREICH
Tel. +43 662 875574-0
Fax +43 662 878677
Verkauf Tel. +43 662 875574-900
Verkauf Fax +43 662 875574-30
E-Mail info@foerch.at
Internet www.foerch.at

Förch Componentes para Taller S.L.
Camino de San Antón, S/N
18102 Ambroz (Granada)
SPANIEN
Tel. +34 902161020
Fax +34 958401787
E-Mail info@forch.es
Internet www.forch.es

Lhomme Tools & Fasteners
Ind. Genk-Noord Zone 3
Gieterijstraat 149 B4
3600 Genk
BELGIEN
Tel +32 89 71 66 61
Fax +32 89 71 59 27
E-Mail: info@lhommetools.be

Ziebe Limited
82 Westcott Venture Park
HP18 0XB Westcott, Aylesbury, Bucks
GROSSBRITANNIEN
Tel +44 12 96 65 52 82
Fax +44 12 96 65 19 47
E-Mail: sales-dept@ziebe.co.uk
Internet: www.ziebe.co.uk

Elmas Otomotiv Turizm Ithalat
Ihracat San Ve Tic Ltd.
2 Gursel
Ikizler Sokak No. 2
80360 Okmeydani/Istanbul
TÜRKEI
Tel. +90 21 22 21 71 71
Fax +90 21 23 68 82 93
E-Mail: info@elmasotomotiv.com
Internet: www.foerch.com

Förch Polska Sp. z o.o.
43-392 MIĘDZYRZECZE GÓRNE 379
POLEN
k/ Bielska-Białej
Tel. +48 33 8196000
Fax +48 33 8158548
E-Mail info@forch.pl
Internet www.forch.pl

Vardalis & Co. EE.K.
11 Km Nat. Rd./Th.Edessa
57008 Thessaloniki
GRIECHENLAND
Tel +30 23 91 02 12 22
Fax +30 23 91 02 12 23
E-Mail: info@forch.gr
Internet: www.foerch.com

Förch Kereskedelmi Kft
Bakony u. 4.
8000 SZÉKESFEHÉRVÁR
UNGARN
Tel. +36 22 348348
Fax +36 22 348355
E-Mail info@foerch.hu
Internet www.foerch.hu

Förch S.p.A.
Via Negrelli 8
39100 BOLZANO
ITALIEN
Tel. +39 0471 204330
Fax +39 0471 204290
E-Mail info@forch.it
Internet www.forch.it

Förch Nederland BV
Zandbreeweg 10 A
7577 BZ Oldenzaal
NIEDERLANDE
Tel. +31 541 751040
Fax +31 541 751041
E-Mail info@foerch.nl
Internet www.foerch.nl

N1
Dalvegur 10-14
201 Kopavogur
ISLAND
Tel. +354 440 11 80
Fax +354 440 10 10
E-Mail: arni@n1.is
Internet: www.n1.is

Förch Slovensko s.r.o.
Rosinská cesta 12
010 08 ŽILINA
SLOWAKEI
Tel +421 41 5002454
Fax +421 41 5002455
E-Mail info@forch.sk
Internet www.forch.sk

Normteknik i Sverige AB
Brännarevägen 1
151 55 Södertälje
SCHWEDEN
Tel. +46 8 55 08 92 64
Fax +46 8 55 08 90 62
E-Mail: info@foerch.de
Internet: www.foerch.se

Förch s.r.o.
Dopravní 1314/1
104 00 PRAHA 10 – Uhříněves
TSCHECHIEN
Tel. +420 271 001 984-9
Fax +420 271 001 994-5
E-Mail info@foerch.cz
Internet www.foerch.cz

Förch d.o.o.
Cesta v Gorice 10a
1000 LJUBLJANA
SLOWENIEN
Tel. +386 1 2442490
Fax +386 1 2442492
E-Mail info@foerch.si
Internet www.foerch.si

4SH PTY LTD.
1/9 Vision Street
6065 Wangara
WESTERN AUSTRALIA
Tel +61 8 93 03 91 13
Fax +61 8 93 03 91 14
E-Mail: sales@4sh.com.au
Internet: www.foerch.com

Förch Portugal Lda
Rua Quinta de Cabanas No. 17
Sćo Vicente
4700-004 Braga
PORTUGAL
Tel. +351 917314442
Fax +351 253339576
E-Mail info@forch.pt
Internet www.forch.pt

Trigers SIA
Straupes Street Iela 3
1073 Riga
LETTLAND
Tel +371 6 7 90 25 15
Fax +371 67 90 24 96
E-Mail: trigers@trigers.lv
Internet: www.trigers.lv

Foermi Handelshaus LLC
Dmitrovskoe Autostrasse
Building 107/18
127247 Moscow
RUSSISCHE FOEDERATION
Tel. 7-495 657 99 57
Fax 7-495 485 87 98
E-Mail: foermi.moscow@foerch.ru
Internet: www.forch.ru

Any abbreviations and acronyms used in this document:

AC Article Categories
acc., acc. to according, according to
ACGIH American Conference of Governmental Industrial Hygienists
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOEL Acceptable Operator Exposure Level
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
BMGV Biological monitoring guidance value (EH40, UK)
BOD Biochemical oxygen demand
BSEF Bromine Science and Environmental Forum
bw body weight
CAS Chemical Abstracts Service
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
COD Chemical oxygen demand
CTFA Cosmetic, Toiletry, and Fragrance Association
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
DT50 Dwell Time - 50% reduction of start concentration
DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ERC Environmental Release Categories
ES Exposure scenario
etc. et cetera
EU European Union
EWC European Waste Catalogue
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
HET-CAM Hen's Egg Test - Chorionallantoic Membrane
HGWP Halocarbon Global Warming Potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC Intermediate Bulk Container
IBC (Code) International Bulk Chemical (Code)
IC Inhibitory concentration
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform ChemicaL Information Database
LC lethal concentration
LC50 lethal concentration 50 percent kill
LCLo lowest published lethal concentration
LD Lethal Dose of a chemical
LD50 Lethal Dose, 50% kill
LDLo Lethal Dose Low
LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAEC No Observed Adverse Effective Concentration
NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene

PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.
These statements were made by:

Chemical Check GmbH, Wöbbeler Straße 2-4, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.

Technical Data Sheet

Printed: 26.09.2013

Article-Description	Article No.
Car Body Stoneguard black L260 1000 ml	**6610 6010**

1. Application:

Car Body Stoneguard is an underbody coating based on synthetic resins and rubber. This underbody coating is quick-drying and especially developed for lasting protection against stone chips for rear aprons, spoilers, door sills, etc.
The product is highly thixotropic, has good adhesion and can be painted over with commercially available coating systems. After applying a closed, elastic film is formed with a lot of structure and with excellent stone chip and corrosion protection.
.

2. Processing:

The surface must be clean, rust-free and dry. The aerosol should be shaken well before use. The product can be processed with all kinds of UBC guns. The optimum processing air pressure is 3-5 bar. Recommended application thickness is up to 1 mm wet film. For later coating with synthetic resin paints the film applied must be nearly completely solidified with 2K and nitrocellulose lacquers. For use with nitro and 2K paints spray a thin layer first and then a second after sufficient airing time. The product must be stored cool.

3. Distance:

Car Body Stoneguard can be removed with solvents such as white spirit, xylene, cold cleaner etc.

4. Physical data:

Colour:	Black	
Viscosity (20°C):	5000 to 9000 mPs	Brookfield RVDV SP.4, 6rpm
	3000 - 5000 mPs	Brookfield RVDV SP.4, 12rpm
Density (20°C):	1:04 ± 0.02 kg / l	DIN 51757
Solids content:	47-51%	DIN 53216
Re-coating:		after complete hardening.
Shelf life:		unopened at least 2 years.

Salt spray test SS according to DIN 53 021 with 5% NaCl. (At 400 microns dry film).
200 hours: rust grade in accordance with DIN 53210 → Ri 0: no rust
Degree of blistering according to DIN 5329 → m0g0: no blisters

The information contained herein is based on the data available at the time of creation of this data sheet (see print date) that are considered in the opinion of Theo Förch GmbH & Co. KG to be reliable. An express or implied warranty as to the accuracy of this data will not be provided. Theo Förch GmbH & Co. KG accepts no responsibility regarding the use of these data or the aforementioned products, processes or devices. You have to decide whether the products are suitable and complete for the intended application, for the protection of the environment and the health and safety of your employees and the users of this material. If we do not have expressly guaranteed in writing specific characteristics and the suitability of the products for a contractually agreed purpose, a technical advice or information, even if they are made in good faith, cannot be binding in any case. This also does not release the buyer from doing own controls, if necessary through a trial.

We strongly recommend that every print design, which is developed to create labels, printed boxes or similar, will be sent to Theo Förch GmbH & Co. KG for review and final approval. This product information replaces any information on the identical product, which was issued before the above-stated date of creation for the above product.

Schutzmaßnahmen

Gemäß § 6 GefStoffV ist der Arbeitgeber verpflichtet, eine Gefährdungsbeurteilung durchzuführen. Diese Gefährdungsbeurteilung muss vor Aufnahme der Tätigkeiten durchgeführt werden. Dabei muss zunächst festgestellt werden, ob die Beschäftigten Tätigkeiten mit Gefahrstoffen durchführen oder ob Gefahrstoffe bei diesen Tätigkeiten entstehen oder freigesetzt werden. Ist dies der Fall, so hat er alle hiervon ausgehenden Gefährdungen für die Gesundheit und Sicherheit der Beschäftigten zu beurteilen. Als Ergebnis dieser Gefährdungsbeurteilung werden die für den Schutz der Beschäftigten Maßnahmen festgelegt. Dabei wird zwischen den allgemein notwendigen Maßnahmen und zusätzlich zu treffenden Maßnahmen unterschieden. Die allgemein notwendigen Maßnahmen müssen bei allen Tätigkeiten mit Gefahrstoffen ergriffen werden. Die gemäß § 8 GefStoffV zu treffenden Maßnahmen haben wir für Sie in einer Checkliste zusammengestellt, die Sie als Anlage zu diesem Dokument finden.

Anlage I Allgemeine und zusätzliche Schutzmaßnahmen

Gehen von dem Produkt weitere Gefahren aus, sind zusätzliche Maßnahmen erforderlich. Diese zusätzlichen Maßnahmen sind in den §§ 9 - 11 GefStoffV beschrieben. Dabei hängen die zusätzlichen Maßnahmen von den Eigenschaften der betroffenen Produkte ab. Die dann zu treffenden Maßnahmen haben wir Ihnen in der Anlage II ebenfalls in einer Checkliste zusammengestellt.

Anlage II Allgemeine Schutzmaßnahmen

Produkte, die Maßnahmen gemäß § 10 GefStoffV erforderlich machen, also krebserzeugende, erbgutverändernde und fruchtbarkeitsgefährdende Gefahrstoffe werden nicht von der Theo Förch GmbH & Co. KG vertrieben.

Zuordnung

Um Ihnen die Entscheidung zu erleichtern, welche Maßnahmen im Arbeitsschutz ergriffen werden müssen (allgemeine Maßnahmen oder allgemeine + zusätzliche Maßnahmen) liefern wir Ihnen entsprechende Hinweise in unserer EDV. Hier sind allen Produkten die erforderlichen Schutzmaßnahmen zugeordnet. Dabei steht

AS für Allgemeine Schutzmaßnahmen und
ZS für Allgemeine und zusätzliche Schutzmaßnahmen

Die Zuordnung der Produkte zu den erforderlichen Schutzmaßnahmen erfolgt aus der Kennzeichnung des Produktes, die im Punkt 2 des Sicherheitsdatenblattes angegeben ist. Hier sind zu jedem vergebenen R-Satz / H-Satz die Schutzmaßnahmen der Gefahrstoffverordnung zugeordnet.

Ist dem Produkt kein R-Satz / H-Satz zugeordnet, erfolgt eine Zuordnung zu den allgemeinen Schutzmaßnahmen gemäß § 8 der Gefahrstoffverordnung (Dieses erfolgt auch für Produkte, bei denen aufgrund Ihrer Kennzeichnung und der geringen Produktmenge (kleiner 125 ml) eine Kennzeichnung mit R-Sätzen / H-Sätzen nicht erforderlich ist.

Die Zuordnung der erforderlichen Schutzmaßnahmen zu den R-Sätzen / H-Sätzen erfolgt nach den folgenden Kriterien:

Allgemeine Schutzmaßnahmen gemäß § 8 GefStoffV

Produkte, die lediglich geringe Gefährdungen hervorrufen können. Hier wurden vor allem Produkte zugeordnet, für die die Vergabe eines Gefahrensymbols, oder eines Piktogramms nicht erforderlich ist.

Zusätzliche Schutzmaßnahmen gemäß § 9 GefStoffV

Für reizende / ätzende / gesundheitsschädliche und giftige Stoffe sowie C/M/R-Stoffe der Kat. 3 sind zusätzlich zu den allgemeinen Schutzmaßnahmen weitere Schutzmaßnahmen erforderlich. Diese Maßnahmen sind im § 9 GefStoffV beschrieben. Wird lediglich mit geringen Mengen umgegangen oder sind die Verfahren so, dass kein Kontakt zu diesen Stoffen besteht, können auch die allgemeinen Schutzmaßnahmen nach § 8 ausreichend sein. Wird hingegen mit größeren Mengen hantiert und besteht direkter Kontakt zu diesen Stoffen, sind die zusätzlichen Schutzmaßnahmen gemäß § 9 erforderlich.

Wichtiger Hinweis

Die Zuordnung der Schutzmaßnahmen erfolgte lediglich aufgrund der Kennzeichnung der verwendeten Produkte. Nicht berücksichtigt wurden dabei Stoffmenge, Exposition und Arbeitsverfahren. Daher stellen die angegebenen Schutzmaßnahmen lediglich eine Empfehlung dar, die den Anwender bei seiner Ermittlungspflicht nach § 6 GefStoffV bzw. § 5 des Arbeitsschutzgesetzes unterstützen sollen. Zur endgültigen Festlegung der notwendigen Schutzmaßnahmen ist eine Gefährdungsanalyse vor Ort notwendig, bei der auch die verwendeten Arbeitsmittel und Verfahren, die Exposition gegen die verwendeten Stoffe, mögliche Wechselwirkungen der eingesetzten Produkte, Brand- und Explosionsgefahren sowie Gefährdungen durch Wartungsaufgaben berücksichtigt werden. Weitere zum Teil sehr ausführliche Erläuterungen zur Vorgehensweise bei der Erstellung der Gefährdungsbeurteilung finden Sie in der TRGS 400 sowie in der BGI 570 bzw. BGI 571.

Allgemeine Schutzmaßnahmen (geringe Gefährdung)

Tätigkeiten mit geringer Gefährdung sind Tätigkeiten, bei denen aufgrund der Arbeitsbedingungen einer nur geringen verwendeten Stoffmenge und einer nach Höhe und Dauer niedrigen Exposition die allgemeinen Maßnahmen gemäß § 8 GefStoffV ausreichen. Zur Festlegung von allgemeinen Maßnahmen nach gemäß § 8 GefStoffV müssen die folgenden Bedingungen zutreffen:

Der verwendete Gefahrstoff darf nicht als giftig, sehr giftig, bzw. krebserzeugend, erbgutverändernd oder fruchtbarkeitsgefährdend (Kategorie 1 oder 2) eingestuft sein. Die bei der Tätigkeit verwendete Stoffmenge muss gering sein. Ein eindeutiger Maßstab für »geringe Menge« lässt sich allgemein nicht angeben, da hierzu auch die gefährlichen Stoffeigenschaften, das Freisetzungsvermögen des Gefahrstoffes und die konkrete Tätigkeit zu berücksichtigen sind. Dabei muss die Exposition nach Höhe und Dauer niedrig sein. Hierbei sind inhalative und dermale Anteile zu berücksichtigen. So liegt z. B. bei Feststoffen eine niedrige inhalative Exposition im Regelfall bei emissionsarmen Verwendungsformen wie Pasten, Wachsen, Granulaten, Pellets, Masterbatches vor.

Tätigkeiten mit Gefahrstoffen in engen Räumen und Behältern sind grundsätzlich keine Tätigkeiten mit geringer Gefährdung.

Die Beurteilung, ob hinsichtlich einer dermalen Exposition die Bedingungen für Tätigkeiten geringer Gefährdung erfüllt sind, kann mit Hilfe der TRGS 401 erfolgen. Aufgrund dieser Vorgaben kann bei Gefahrstoffen, die das Symbol „ätzend“ (R34, R35) tragen, eine Tätigkeit geringer Gefährdung nicht vorliegen, wenn ein Hautkontakt nicht ausgeschlossen werden kann.

Beispiele für Tätigkeiten geringer Gefährdung sind:

Verwendung von Gefahrstoffen, die für den privaten Endverbraucher im Einzelhandel in Selbstbedienung erhältlich sind, z. B. Ausbesserung kleiner Lackschäden mit Lackstiften oder die Verwendung und Aufbewahrung haushaltsüblicher Mengen von Klebstoffen im Haushalt. Auch wenn bei einer Tätigkeit nicht alle Bedingungen nach Absatz 2 erfüllt sind, so kann die Gefährdungsbeurteilung trotzdem zu einer Festlegung von Maßnahmen führen, die weitgehend dem § 8 GefStoffV entsprechen. In diesen Fällen sind jedoch weitere organisatorische Anforderungen zu beachten, insbesondere zum Führen eines Gefahrstoffverzeichnisses, der Erstellung einer Betriebsanweisung, der Dokumentation der Gefährdungsbeurteilung und zur arbeitsmedizinischen Vorsorge.

Bei Tätigkeiten mit geringer Gefährdung sind die folgenden Schutzmaßnahmen zu beachten:

- Nur die vom Arbeitgeber vorgesehenen Gefahrstoffe verwenden.
- Nur die benötigten Gefahrstoffe am Arbeitsplatz aufbewahren.
- Arbeitsplatz aufräumen sowie Arbeitsgeräte und Werkzeuge sauber halten.
- Verunreinigungen durch Gefahrstoffe sofort beseitigen.
- Rückstände von Gefahrstoffen an Behältern entfernen.
- Gefahrstoffe so aufbewahren, dass Missbrauch und Fehlgebrauch verhindert werden.
- Gefahrstoffe möglichst in der Originalverpackung aufbewahren.
- Gefahrstoffe nicht in solchen Behältern aufbewahren oder lagern, durch deren Form oder Inhalt Gefahrstoffe mit Lebensmitteln verwechselt werden können.
- Gefahrstoffe nicht in der Nähe von Arzneimitteln, Lebensmitteln oder Futtermitteln aufbewahren
- Zur Vermeidung einer inhalativen Belastung ist im Regelfall eine natürliche Lüftung ausreichend.

Zusätzliche Schutzmaßnahmen gemäß § 9 GefStoffV

Der Arbeitgeber hat Maßnahmen so festzulegen, dass die durch einen Gefahrstoff bedingte Gefährdung der Gesundheit und Sicherheit der Beschäftigten bei der Arbeit beseitigt oder auf ein Minimum reduziert wird. Es gilt das Substitutionsgebot, das heißt, falls Produkte verfügbar sind, von denen eine geringere Gefährdung ausgeht, sind diese Produkte zu verwenden. Lässt sich die Gefährdung nicht beseitigen, hat der Arbeitgeber diese durch Maßnahmen nach dem Stand der Technik und einer guten Arbeitspraxis in der nachstehenden Rangordnung auf ein Minimum zu verringern:

- Gestaltung geeigneter Verfahren und technischer Steuerungseinrichtungen sowie Verwendung geeigneter Arbeitsmittel und Materialien,
- Durchführung kollektiver Schutzmaßnahmen an der Gefahrenquelle, wie zum Beispiel angemessene Be- und Entlüftung und geeignete organisatorische Maßnahmen. Die Gefährdung ist auf ein Minimum reduziert, wenn z. B.
    - der Stand der Technik eingehalten wird,
    - ein Arbeitsplatzgrenzwert eingehalten wird,
    - Hautkontakt verhindert wird,
    - die Bildung explosionsfähiger Atmosphäre verhindert wird oder
    - Zündquellen beseitigt sind.

Kann eine Gefährdung nicht durch diese Maßnahmen beseitigt werden, sind individuelle Schutzmaßnahmen, wie das Tragen von persönlicher Schutzausrüstung notwendig.

Gemäß § 14 GefStoffV sind die Beschäftigten auf der Basis der schriftlich vorliegenden Betriebsanweisung mindestens einmal jährlich mündlich zu unterweisen. Die Mindestangaben zur schriftlichen Betriebsanweisung und die Mindestforderungen zur Unterweisung sind in der TRGS 555 „Betriebsanweisung und Information der Beschäftigten“ aufgeführt.

Für bestimmte Tätigkeiten sind arbeitsmedizinische Vorsorgeuntersuchungen notwendig. Die Tätigkeiten und Stoffe für die das gilt, sind in den §§ 15, 16 und dem Anhang V GefStoffV aufgeführt.

Weitere Unterstützung bei der Festlegung der betrieblichen Grundmaßnahmen bieten die Schutzleitfäden der Reihe 200 (siehe www.baua.de und www.bgchemie.de).

Firmenlogo	**Erfassung der erforderlichen Schutzmaßnahmen** Allgemeine und zusätzliche Schutzmaßnahmen nach §§ 8, 9 und 11 GefStoffV **- Gefährdungsbeurteilung - Dokumentation -**	Datum: Betrieb:
Tätigkeit/Personen:		
Gefahrstoffe		

Anforderung nach §§ 8, 9 und 11 GefStoffV

Nr.	Maßnahmen	Erfüllt		Schutzmaßnahmen (technisch-organisatorisch-persönlich)	Beratungs bedarf	Realisierung		Wirksamkeit	
		ja	nein			Bis wann	durch	wirksam	wann
1.	**Informationsermittlung und innerbetriebliche Kennzeichnung**								
1.1.	Gefahrstoffverzeichnis liegt vor	☐	☐						
1.2.	Sicherheitsdatenblätter sind vorhanden, aktuell (2)	☐	☐						
1.3.	Sicherheitsdatenblätter sind den Mitarbeitern zugänglich (2)	☐	☐						
1.4.	Gefahrstoffe sind eindeutig gekennzeichnet (2)	☐	☐						
1.5.	Rohrleitungen und Anlagenteile sind eindeutig gekennzeichnet	☐	☐						
2.	**Arbeitsstätte**								
2.1.	Eine gute allgemeine Lüftung, ggf. technische Lüftung ist vorhanden	☐	☐						
2.2.	Pausenräume und Bereitschaftsräume stehen zur Verfügung (2)	☐	☐						
2.3.	Waschgelegenheiten mit Handtüchern sind vorhanden	☐	☐						
2.4.	Reinigungsmittel, Hautschutz- und Hautpflegemittel sind vorrätig	☐	☐						
2.5.	Umkleideräume und Kleiderablagen stehen zur Verfügung (2)	☐	☐						
2.6.	Die Arbeitsplätze werden regelmäßig gereinigt	☐	☐						
2.7.	Technische Schutzmaßnahmen werden spätestens jedes dritte Jahr geprüft und dokumentiert	☐	☐						
3.	**Arbeitsverfahren**								
3.1.	Es wurde eine Substitutionsprüfung durchgeführt (2)	☐	☐						
3.2.	Es werden Arbeitsverfahren angewendet, die möglichst wenig Gase, Dämpfe, Stäube und Aerosole verursachen	☐	☐						
3.3.	Es werden geeignete Arbeitsmittel, Geräte und Anlagen bereitgestellt	☐	☐						
3.4.	Die Anzahl der Exponierten ist auf ein Minimum reduziert	☐	☐						
3.5.	Die Rangfolge der Schutzmaßnahmen wurde eingehalten (2)	☐	☐						
3.6.	Gebinde sind geschlossen und werden nur zur Entnahme geöffnet	☐	☐						

Firmenlogo	**Erfassung der erforderlichen Schutzmaßnahmen** Allgemeine und zusätzliche Schutzmaßnahmen nach §§ 8, 9 und 11 GefStoffV **- Gefährdungsbeurteilung - Dokumentation -**	Datum: Betrieb:
Tätigkeit/Personen:		
Gefahrstoffe		

Anforderung nach §§ 8, 9 und 11 GefStoffV

Nr.	Maßnahmen	Erfüllt		Schutzmaßnahmen (technisch-organisatorisch-persönlich)	Beratungs bedarf	Realisierung		Wirksamkeit	
		ja	nein			Bis wann	durch	wirksam	wann
3.7.	Die Dauer und das Ausmaß der Exposition ist auf das erforderliche Maß beschränkt	☐	☐						
3.8.	Bei Abfüll- und Umfüllvorgängen wird ausreichend belüftet und abgesaugt	☐	☐						
3.9.	Ablagerungsmöglichkeiten für Stäube sind gering gehalten	☐	☐						
3.10.	Verspritzen von Flüssigkeiten wird vermieden	☐	☐						
4.	**Organisation**								
4.1.	Gefahrstoffmenge am Arbeitsplatz wird gering gehalten	☐	☐						
4.2.	Arbeitsmittel und Stoffe werden bestimmungsgemäß verwendet	☐	☐						
4.3.	Die Beschäftigten werden mindestens einmal jährlich unterwiesen	☐	☐						
4.4.	Die Unterweisung schließt eine arbeitsmedizinisch-toxikologische Beratung ein (2)	☐	☐						
4.5.	Betriebsanweisungen sind vorhanden und den Beschäftigten bekannt (2)	☐	☐						
4.6.	Bei Alleinarbeit ist eine angemessene Aufsicht gewährleistet (2)	☐	☐						
4.7	Arbeitsplatzgrenzwerte (AGW) werden eingehalten (2)	☐	☐						
4.7.	Bei Stoffen ohne AGW wurde die Wirksamkeit der Schutzmaßnahmen nachgewiesen (2)	☐	☐						
4.8.	Arbeitsmedizinische Vorsorgeuntersuchungen wurden veranlasst (2)	☐	☐						
4.9.	Arbeitsmedizinische Vorsorgeuntersuchungen wurden angeboten (2)	☐	☐						
4.10.	Nachuntersuchungen werden regelmäßig durchgeführt (2)	☐	☐						
5.	**PSA**								
5.1.	PSA gegen inhalative und dermale Gefährdungen ist geeignet und verwendungsfähig	☐	☐						
5.2.	Das Tragen von belastender PSA ist zeitlich auf ein Mindestmaß beschränkt (2)								
5.3.	PSA gegen physikalisch-chemische Gefährdungen ist geeignet	☐	☐						

Firmenlogo	**Erfassung der erforderlichen Schutzmaßnahmen** Allgemeine und zusätzliche Schutzmaßnahmen nach §§ 8, 9 und 11 GefStoffV **- Gefährdungsbeurteilung - Dokumentation -**	Datum: Betrieb:
Tätigkeit/Personen:		
Gefahrstoffe		

Anforderung nach §§ 8, 9 und 11 GefStoffV

Nr.	Maßnahmen	Erfüllt		Schutzmaßnahmen (technisch-organisatorisch-persönlich)	Beratungs bedarf	Realisierung		Wirksamkeit	
		ja	nein			Bis wann	durch	wirksam	wann
6.	**Hygiene und Hautschutz**[1)]								
6.1.	Arbeitskleidung sollte getragen werden	☐	☐						
6.2.	Essen, Trinken, Rauchen sollte am Arbeitsplatz verboten werden	☐	☐						
6.3.	Kontaminationen und Verschmutzungen der Haut werden sofort entfernt	☐	☐						
6.4.	Verschmutzte Arbeitsbekleidung wird ausgewechselt	☐	☐						
6.5.	Staubige Arbeitsbekleidung wird gereinigt	☐	☐						
6.6.	Es liegt ein Hautschutzplan vor	☐	☐						
6.7.	Es erfolgt eine getrennte Aufbewahrung von Straßen- und Arbeitsbekleidung (2)	☐	☐						
7.	**Sauberkeit und Reinigung**								
7.1.	Arbeitsplätze werden regelmäßig aufgeräumt	☐	☐						
7.2.	Arbeitsplätze/Arbeitsbereiche werden regelmäßig gereinigt	☐	☐						
7.3.	Arbeitsmittel, Geräte und Gebinde werden gereinigt und sauber gehalten	☐	☐						
7.4.	Abfallbehältnisse zur ordnungsgemäßen Entsorgung stehen bereit	☐	☐						
7.5.	Restmengen oder leere Gefahrstoffgebinde werden sicher gelagert und sachgerecht entsorgt	☐	☐						
8.	**Aufbewahrung und Lagerung**[2)]								
8.1.	Die Lagerung ist übersichtlich	☐	☐						
8.2.	Eindeutige Lagerorte sind vorhanden (2)	☐	☐						
8.3.	Keine Aufbewahrung und Lagerung in Lebensmittelbehältnissen	☐	☐						
8.4.	Keine Aufbewahrung und Lagerung neben Arznei-, Futter- und Lebensmitteln	☐	☐						
8.5.	Staubarme bzw. flüssigkeitsdichte (Dampfdichte) Lagerung	☐	☐						
9.	**Physikalisch-chemische Gefährdungen**								
9.1.	Bei Tätigkeiten mit Stoffen, die zu Brand- und	☐	☐						

Firmenlogo	**Erfassung der erforderlichen Schutzmaßnahmen** Allgemeine und zusätzliche Schutzmaßnahmen nach §§ 8, 9 und 11 GefStoffV **- Gefährdungsbeurteilung - Dokumentation -**	Datum: Betrieb:
Tätigkeit/Personen:		
Gefahrstoffe		

Anforderung nach §§ 8, 9 und 11 GefStoffV

Nr.	Maßnahmen	Erfüllt		Schutzmaßnahmen (technisch-organisatorisch-persönlich)	Beratungs bedarf	Realisierung		Wirksamkeit	
		ja	nein			Bis wann	durch	wirksam	wann
	Explosionsgefahren führen können, wurden weitere Maßnahmen getroffen								
9.2.	Bei Tätigkeiten mit Stoffen, deren physikalisch-chemische Eigenschaften zu weiteren Gefährdungen führen können, wurden weitere Maßnahmen getroffen	☐	☐						

Bemerkungen	1) Bezieht sich auf alle Tätigkeiten mit erhöhter Staubentwicklung, spritzenden Arbeitsverfahren oder sonstigen Arbeitsplätzen mit erhöhter Stoffbelastung. 2) Bezieht sich auf alle chemischen Arbeitsstoffe.

Erfassung der erforderlichen Schutzmaßnahmen nach §§ 8,9 und 11 GefStoffV

Anmerkungen zu:

Spalte 2: „Maßnahmen“

Aus den Inhalten der Gefahrstoffverordnung wurden die erforderlichen Maßnahmen nach den Schutzstufen zusammengestellt. Ist in dem entsprechenden Arbeitsbereich die Schutzstufe 2 anzuwenden, so dient diese Spalte als Checkliste für die geforderten Schutzmaßnahmen. Die vorliegende Checkliste nach der Schutzstufe 2 *plus* beinhaltet darüber hinaus die Forderungen zu dermalen und physisch-chemischen Gefährdungen.

Spalte 3: „Erfüllt“
Ist die Maßnahme noch nicht umgesetzt, besteht eine potentielle Gefährdung/ Belastung für die Mitarbeiter, die durch entsprechende Schutzmaßnahmen (technisch-organisatorisch-persönlich) zu beseitigen sind.

Spalte 4: „Schutzmaßnahmen“
Wurde in Spalte 3 „nein" eingetragen: Ist in Spalte 4 die betreffende Maßnahme aus der Spalte 2 als umzusetzende Schutzmaßnahme zu konkretisieren.
Wurde in Spalte 3 „ja" eingetragen: Können in Spalte 4 auch bereits realisierte Maßnahmen kommentiert werden, ggf. auch auf vorhandene Unterlagen verwiesen werden.

Spalte 5:
Beratungsbedarf kann nötig sein, wenn Unsicherheiten bei der Erfüllung (Spalte 2) oder Bewertung (Spalte 3) der Gefährdungen oder bei der Maßnahmenfestlegung (Spalte 4) bestehen.

Spalte 6:
Die Realisierung der Maßnahmen wird von der verantwortlichen Führungskraft kontrolliert.

Spalte 7:
Wirksamkeit von Maßnahmen z. B. bei Begehungen, Audits, Sicherheitsbegehungen kontrollieren.